



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE NO.: 2025011002802322

NAME AND ADDRESS OF THE APPLICANT

Eaglerise Electric & Electronic (Ji An) Co., Ltd.
Southwest Corner, Crossing Between Panlong Road And Chaoyang Road, Industrial Park, Ji An
County, Jiangxi Province, P.R.China

NAME AND ADDRESS OF THE MANUFACTURER

Eaglerise Electric & Electronic (Ji An) Co., Ltd.
Southwest Corner, Crossing Between Panlong Road And Chaoyang Road, Industrial Park, Ji An
County, Jiangxi Province, P.R.China

NAME AND LOCATION OF THE FACTORY

Eaglerise Electric & Electronic (Ji An) Co., Ltd.
Southwest Corner, Crossing Between Panlong Road And Chaoyang Road, Industrial Park, Ji An
County, Jiangxi Province, P.R.China

PRODUCT NAME,MODEL AND SPECIFICATION

A.C. Supplied Electronic Controlgear for LED Modules (LED Controlgear, Independent, Constant
Current Mode, Auto-wound Controlgear, Class I, IP66+IP67, ta:50°C/60°C, tc:90°C, Suitable for
Direct Mounting on Normally Flammable Material Surfaces, Temperature Declared Thermally
Protected: 110°C, Controlled Port Dimming)
See Appendix. 120-277V ~ 50/60Hz

STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB 17625.1-2022;GB/T 17743-2021;GB 19510.1-2009;GB 19510.14-2009

This is to certify that the above mentioned product(s) complies with the requirements of
implementation rules for compulsory certification(REFNO. CNCA-C10-01:2014).

Valid from: Aug.12,2025

Valid until: Aug.11,2030

The certificate information and validity could be checked by scanning the QR code below or logging in to
the website of the issuing authority, or on the website of the CNCA (www.cnca.gov.cn).



SIGNATURE:

谢肇煦



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.





CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2025011002802322

Appendix: Page 1 of 1

序号	型号	输出电压 (VDC)	输出电流 (mA) (恒流)	最大输出功率(W)Max	最大输出电压 (VDC) Max
1.	RMX-150-1200 IP67 0-10 L	71-214	500-1200	150	250
2.	RMX-200-1200 IP67 0-10 L	142-286	500-1200	200	400
3.	RMX-250-1200 IP67 0-10 L	165-357	500-1200	250	400
输入:120-277V~ 50/60Hz ta:50℃(输入电压120-190V~); ta:60℃ (190-277V~) 调光方式: 0-10V、外接可调电阻					

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

This page is attached to the certificate and should be used at the same time as the certificate page.



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.