



Ref. Certif. No

NO135826

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT  
(IECEE) CB SCHEME

## CB TEST CERTIFICATE

## Product

LED Power Supply

## Name and address of the applicant

EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD  
West Zone, Ji An County Industrial Park, Ji an County  
Jiangxi Province  
China

## Name and address of the manufacturer

EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD  
West Zone, Ji An County Industrial Park, Ji an County  
Jiangxi Province  
China

## Name and address of the factory

EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD  
West Zone, Ji An County Industrial Park, Ji an County  
Jiangxi Province  
China

Note: When more than one factory, please report on page 2

☐ Additional Information on Page 2Ratings and Principal characteristics  
Trademark /Brand (If any)PRI: max. 0.25 A, 220-240 V~, 0/50/60 Hz See additional information for more ratings.  
EAGLERISE

## Customer's Testing Facility (CTF) Stage used

## Model/Type Ref

FLS-15-350 LD1 ADV, FLS-21-500 LD1 ADV, FLS-30-750 LD1 ADV, FLS-40-1050 LD1 ADV,  
FLS-8-500 DALI-2 LA ADV, FLS-12-700 DALI-2 LA ADVAdditional information (If necessary may also be  
reported on Page 2)☒ Additional Information on Page 2A sample of the product was tested and found  
to be in conformity withIEC 61347-1:2015, IEC 61347-1:2015/AMD1:2017  
IEC 61347-2-13:2014, IEC 61347-2-13:2014/AMD1:2016As shown in the Test Report Ref. No. which  
forms part of this Certificate

REP110324

This CB Test Certificate is issued by the National Certification Body

Philip Pedersen vei 11,  
NO-1366 Lysaker, Norway  
Date: 27-08-2025

Jiyea Gim

Signature: Jiyea Gim  
Certification department



Ref. Certif. No

NO135826

### Additional Information (if necessary)

Centralized emergency power supply: 220-240 V DC

SEC: max. 42 W, max. 1.05 A, 2.5-49 Vd.c. (under load), max. 60 Vd.c. (no-load),

EOF1: 100% (For FLS-15-350 LD1 ADV, FLS-21-500 LD1 ADV, FLS-30-750 LD1 ADV and FLS-40-1050 LD1 ADV),

EOF1: 85% (For FLS-8-500 DALI-2 LA ADV and FLS-12-700 DALI-2 LA ADV)

Independent type, Class II, SELV, constant current output, thermal protected 110 °C, ta: 45 °C, tc: 80 °C



Philip Pedersen vei 11,  
NO-1366 Lysaker, Norway

Date: 27-08-2025

Jiyea Gim

Signature: Jiyea Gim  
Certification department