


12W Constant Current Power Supply



■ Approve



Features

- For luminaires of protection Class II, SELV, Independent
- Input Voltage: 220-240VAC
- Protections: SCP/OLP/OVP/OTP
- Power Factor: 0.95(Typ.)
- Efficiency: $\geq 92\%$
- 5 years warranty
- IP20

Applications


- LED panel

◆ Description

LS-12-XXX LI1 ADV is a 12W constant current LED driver with 200 to 350mA output current and a forward voltage range from 24 to 40Vdc. With it's compact dimensions from 116 x 41 x 26 mm. It is easy to integrate in LED Panel products. The side covers are available as accessories and allow to use the LED driver independent.

◆ Model code

LS-12-XXX LI1 ADV



◆ Specification

Output	Constant Current (mA)	200mA	250mA	300mA	350mA
	Voltage Range(VDC)	24-40VDC			
	Unload voltage Max.(VDC)	59VDC			
	Current Accuracy	±8%		±5%	
	Output LF current ripple(≤120Hz)	≤±3%			
	SVM	≤0.4@Full Load,230V			
	Pst	≤1@Full Load,230V			
	Efficiency(Typ.)	≥92% @Full Load,230V			
Input	Rated input voltage(VAC)	220-240V			
	Range of input voltage(VAC)	198-264VAC			
	Maximum voltage	300VAC@1 h maximum,unit might not operate in this abnormal condition			
	Range of input voltage(VDC)	176-280VDC			
	Frequency(Hz)	0/50/60 Hz			
	Displacement factor	0.95 @Full Load,230V			
	Power Factor	0.95 @Full Load,230V			
	Input Current max	0.1A Max.			
	Start-up time	< 0.5S			
	No Load Power	≤0.5W			
	THD (Typ.)	<10% @Full Load,230V			
Protection	Over Load Protection	103-120%			
		YES/Auto Resume			
	Over Voltage Protection	>59V			
		YES/Auto Resume			
	Short circuit Protection	YES/Auto Resume			
capability	Surge capability (L-N)	1KV			
	Surge capability (L/N-Ground)	NA			
Environment	Operating Temperature	-20℃~+45℃			
	Humidity	20%-90%RH			
	Tc	80℃			
	Storage Temperature	-25℃~+60℃			
	Life time	> 50000h@Tc=80℃,230VAC			
	Ripple&Noise	≤20dB(A)@10cm			
Surface	Dimension	116X41X26mm			
	material	PC			
Standards	Safety	GB19510. 1, GB19510. 14;IEC61347- 1, IEC61347-2- 13;EN61347- 1, EN61347-2-13; EN62384;			
	EMC	GB/T17743, GB17625. 1;EN55015, EN61000-3-2, EN61000-3-3, EN61547:EN61000-4-2,3,4,5,6,8,11, EN61547:EN61000-4-5			

	Energy Efficiency	Erp2.0 EU 2019/2020
	RoHS	RoHS (2011/65/EU) (EU)2015/863
Note	1.All parameters not specially mentioned are measured at 230VAC input , full load and 25°C of ambient temperature. 2.Ripple & Noise are measured at 20MHz of bandwidth by using a 300mm twisted pair-wire terminated with a 0.1uF & 47 uF parallel capacitor. 3.Switch and dimmer are not recommended to connect between this product output and luminaries. 4.The DC input for this product is only used for emergency lighting and applies to functional and safety requirements, EMC is not considered. 5.The over-temperature protection of the product is provided by the IC.	


◆ Parameter

Number	Model number	Output			
		Current (mA)	Voltage (VDC)	Voltage No load (VDC)	Power (W)
1	LS-12-200 LI1 ADV	200mA	24-40VDC	59VDC	8
2	LS-12-250 LI1 ADV	250mA			10
3	LS-12-300 LI1 ADV	300mA			12
*4	LS-12-350 LI1 ADV	350mA			14

* Factory default

◆ Inrush Current


I _{peak}	T _{width}	B10	B16	B20	C10	C16	C20
23.2A	128μs	28pcs	45pcs	56pcs	47pcs	75pcs	94pcs




Remarks:

- 1.The number of drives mounted under different MCBs in the table is the maximum value. Please do not exceed this number during installation.
- 2.Different brands and models of miniature circuit breakers, the number of drives mounted will be slightly different.

◆ Wiring diagram



◆ 2D diagram



◆ Wiring & Connections

Specification item		Value (Unit)
Input	Input wire cross-section	0.5...1.5 mm ²
	Input wire gauge.	16...20 AWG
	Input wire strip length	7...9mm
Output	Output wire cross-section	0.5...1.5 mm ²
	Output wire gauge.	16...20 AWG
	Output wire strip length	7...9mm


Note: Solid wire is risky to use on an angled terminal. Stranded wire is recommended for this kind of use.

◆ Packaging


Model	Product Dimensions(mm)	weight/piece	Outer carton dimension(mm)	Quantity/carton	Net weight/carton(Kg)	Gross weight/carton(Kg)
LS-12-XXX LI1 ADV	116X41X26	0.085	370X275X215	126	10.71	11.71

◆ Curve for LS-12-350 LI1 ADV, $I_o=350\text{mA}$


Lifetime vs. Temperature Curve




Efficiency vs. Load




Power Factor Characteristics



THD vs. Load



◆ Operating window



— Operating window 100%

◆ Revision Updates

ITEM	BEFORE	AFTER	VERSION	DATE
Initial			A	2025/08/30
Curve		Update	B	2025/11/18

Remark: The final interpretation of the contents of the specification belongs to Eaglerise Electric & Electronic (China) Co., Ltd.

Tel: +86-0757-86256822, +86-0757-86256831

E-mail: sales@eaglerise.com

Website : <https://lighting.eaglerise.com>

