

ATTESTATION OF CONFORMITY

Issued to: EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD
West Zone, Ji An County Industrial Park, Ji An County, Jiangxi, China

For the product: LED driver

Trade name: 

Type/Model: See annex

Ratings: 220-240 Vac, 50/60Hz
Details refer to annex

Manufactured by: EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD
West Zone, Ji An County Industrial Park, Ji An County, Jiangxi, China

Subject: Complete evaluation of electrical system of the appliances

Requirements: EN IEC 55015:2019 + A11:2020
EN IEC 61547:2023
EN IEC 61000-3-2:2019 + A1:2021 + A2:2024
EN 61000-3-3:2013 + A1:2019 + A2:2021 + AC:2022-01

This Attestation is granted on account of an examination by DEKRA, the results of which are laid down in a test file / test report no 4944529.50.

This Attestation implies that the examined types are in accordance with the standards designated under the Electromagnetic Compatibility Directive (EMC) 2014/30/EU.

The examination has been carried out on one single specimen or several specimens of the product, submitted by the manufacturer. The Attestation does not include an assessment of the manufacturer's production. Conformity of this production with the specimen tested by DEKRA is not the responsibility of DEKRA.

This document does not authorize the use of any DEKRA approved mark.

Arnhem, 14 November 2025

Number: 4944529.01AOC

DEKRA Testing and Certification (Shanghai) Ltd.,
Guangzhou Branch



Miranda Zhou
Certification Manager

© Integral publication of this attestation and adjoining reports is allowed

Annex

Document no. : 4944529.01AOC

Type/Model/Ratings:

Model	Input					Output			
	U _n	I _{n Max}	f _n	PF (AC input)	P _n	I _{rated}	U _{rated}	U _{out}	P _{rated}
	(Vac)	(mA)	(Hz)		(W)	(mA)	(Vdc)	(Vdc)	(W)
LS-40-600 LI1 EXC S	220- 240	170	50/60	0,9C- 0,95	31,02	600	27-42	59	25,2
LS-40-650 LI1 EXC S		190			33,61	650			27,3
LS-40-700 LI1 EXC S		200			36,19	700			29,4
LS-40-750 LI1 EXC S		220			38,78	750			31,5
LS-40-800 LI1 EXC S		230			41,36	800			33,6
LS-40-850 LI1 EXC S		250			43,95	850			35,7
LS-40-900 LI1 EXC S		260			45,49	900			37,8
LS-40-950 LI1 EXC S		270			48,01	950			39,9
LS-40-1000 LI1 EXC S		270			48,13	1000			27-40
LS-40-1050 LI1 EXC S		290			48,01	1050	27-38		39,9

End