



Ref. Certif. No

NO135421

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT  
(IECEE) CB SCHEME

## CB TEST CERTIFICATE

## Product

LED Power Supply

## Name and address of the applicant

EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD  
West Zone, Ji An County Industrial Park, Ji an County  
Jiangxi Province  
China

## Name and address of the manufacturer

EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD  
West Zone, Ji An County Industrial Park, Ji an County  
Jiangxi Province  
China

## Name and address of the factory

EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD  
West Zone, Ji An County Industrial Park, Ji an County  
Jiangxi Province  
China

Note: When more than one factory, please report on page 2

☐ Additional Information on Page 2

## Ratings and Principal characteristics

PRI: max. 0.22 A, 220-240 V~, 50/60 Hz  
SEC: max. 33.6 W, max. 0.8 A, 24-42 Vd.c. (under load),  
max. 59 Vd.c. (no-load).

## Trademark /Brand (If any)

EAGLERISE



## Customer's Testing Facility (CTF) Stage used

## Model/Type Ref

CS-xx-yyy SB, CS-xx-yyy LB

## Additional information (If necessary may also be reported on Page 2)

☒ Additional Information on Page 2

## A sample of the product was tested and found to be in conformity with

IEC 61347-1:2015, IEC 61347-1:2015/AMD1:2017  
IEC 61347-2-13:2014, IEC 61347-2-13:2014/AMD1:2016

## As shown in the Test Report Ref. No. which forms part of this Certificate

REP104830

This CB Test Certificate is issued by the National Certification Body

Philip Pedersen vei 11,  
NO-1366 Lysaker, Norway

Date: 17-07-2025

Signature: Okhyun Jeon  
Certification department



Ref. Certif. No

NO135421

### Additional Information (if necessary)

Built-in LED power supply with double or reinforced insulation, providing SELV output, constant current output, thermally protected 110 °C, ta: 70 °C, tc: 100 °C

CS-xx-yyy SB:

The 'xx' in the type designation can be 8 or 15.

The 'yyy' is for the output current and represents the number from 100 to 400, for example, 100 means the output current is 100 mA, 400 means the output current is 400 mA.

CS-xx-yyy LB:

The 'xx' in the type designation can be 25 or 32.

The 'yyy' is for the output current and represents the number from 450 to 800, for example, 450 means the output current is 450 mA, 800 means the output current is 800 mA.



Philip Pedersen vei 11,  
NO-1366 Lysaker, Norway

Date: 17-07-2025

Signature: Okhyun Jeon  
Certification department