ITS FIX N CS L Series LED Power Supply

OSRAM

LED Drivers

ITS FIX 65/220-240/350 N CS L

65W Constant Current LED driver

Applications

Linear light

Approvals

Housing material: metal, white

* image for information purpose only

Product Features

- For luminaire of protection class I
- Non-isolated design
- Output current range: 200 - 350 mA
- Urated: 70 - 200 V
- For built-in use
- Input Voltage：220 - 240 Vac
- Power Factor：0.95 (Typ.)
- Efficiency up to 94 %
- Suitable for emergency lighting acc. to EN 50172
- Adjustable Output Current with DIP switch
- Ta range: -20...+60 ℃
- Surge capability: 2 kV
- 5 years guarantee
- Protection: SCP / OLP / OVP / OTP

Electrical specification

Input

Item	Value
Rated input voltage (V)	220 - 240 V
Range of input voltage (AC)	198 - 264 Vac
Range of input voltage (DC)	176 - 280 Vdc
Maximum voltage	300 Vac @ 1h maximum, the unit may not operate under this abnormal condition
Input Current Max.	0.38 A
Frequency	0 / 50 / 60 Hz
Total Harmonic Distortion (THD)	< 10 % @ Full load, 230 Vac, 50 Hz. See graphs
Power factor	0.95 @ Full load, 230 Vac, 50 Hz. See graphs
Displacement Factor	≥ 0.95 @ Full load, 230 Vac, 50 Hz
Start-up time (AC)	< 0.5 s
Start-up time (DC)	< 0.6 s
Switch over time (AC / DC mode)	< 0.6 s
No-load power	≤ 0.5W @ 220 Vac

Output

Item	Value
Constant Current	200 - 350 mA
Voltage Range	70 - 200 Vdc @ 200 - 300mA; 70 - 185 Vdc @ 350 mA
Unload voltage Max.	250 Vdc
Current accuracy	± 5 %
Output current ripple (≤ 120Hz)	± 3 %
Output power range	14 - 65 W
SVM	≤ 0.4 @ Full load, 230 Vac
Pst	≤ 1 @ Full load, 230 Vac
Efficiency	94 % @ Full load, 230 Vac, 50 Hz. See graphs
EOFi	100 %
Galvanic isolation	Non-isolated

Protection

Item	Value
Over Load Protection	> 103 % / Auto recovery
Over Voltage Protection	> 250 V / Auto recovery
Short Circuit Protection	Auto recovery
Over Temperature Protection	Auto recovery

Surge capability

Item	Value
Surge capability (L - N)	2 kV
Surge capability (L / N - Ground)	2 kV

Withstand voltage

Item	Value
Input - Ground	1500 V / 5 mA / 60 s
Output - Ground	500 V / 5 mA / 60 s

Environment

Item	Value
Ambient temperature range ta	-20 ... +60 ℃
Maximum case temperature tc	85 ℃
Storage temperature range	-40 ... +85 ℃
Lifetime	> 100,000 h @ tc=70 ℃ > 50,000 h @ tc=80 ℃
Noise	≤ 20 dB(A) @ 20 cm
Max. case temperature in fault condition	110 ℃
Humidity	20 % - 90 % RH
IP protection class	IP 20
Mains switching cycles	> 25000 cycles
Max. cable length to lamp / LED module	2 m

Dimension

Item	Value
Length	210 mm
Width	30 mm
Height	21 mm

Output technical parameter

Number	Current (mA)	Voltage (Vdc)	Power (W)	PIN1	PIN2	Ambient temperature range ta
1	200 mA	70 - 200 Vdc	40.0 W	--	--	-20 ... +60 ℃
2	250 mA	70 - 200 Vdc	50.0 W	ON	--	-20 ... +60 ℃
3	300 mA	70 - 200 Vdc	60.0 W	--	ON	-20 ... +60 ℃
*4	350 mA	70 - 185 Vdc	64.8 W	ON	ON	-20 ... +60 ℃

* Factory default

Inrush Current & Circuit Breaker

I_{peak}	T_{width}	B10	B16	B20	C10	C16	C20
41.8 A	170 µs	11 pcs	18 pcs	23 pcs	19 pcs	31 pcs	38 pcs

Notes:
1. The values in the table are the maximum number of drives that can be connected to each type of MCB. Do not exceed these values during installation.
2. The allowable number may vary slightly depending on the brand and model of the miniature circuit breaker (MCB).
3. Ipeak = peak inrush current; Twidth = half-peak pulse width. See the figure below for the waveform.



2D diagram



Wiring diagram



Notes:

- To ensure good EMC conditions, the output cables of the LED driver should be routed separately from the mains input connections and mains cables.
- LED wiring should be kept as short as possible to ensure good EMC performance. The max.cable length to lamp / LED module is 2 m.
- To comply with EMC regulations, the secondary side wires (connecting to the LED module) shall be routed in parallel.
- The LED driver does not provide reverse polarity protection on the secondary side. Reverse polarity may damage LED modules that lack reverse polarity protection.
- Wrong wiring may cause malfunction or irreparable damage to the LED driver.

Wiring & Connections

Specification item	Value (Unit)
Input wire cross-section	s: 0.5 ... 1.5 mm^2 f: 0.75 ... 1.5 mm^2
Input wire strip length	7 ... 9 mm
Output wire cross-section	0.5 ... 1.5 mm^2
Output wire strip length	7 ... 9 mm

"s" stands for solid wire, "f" stands for multi-stranded wire.

Recommended wire

Wire cross-section	Wire type
2*0.5 mm^2	H03VVH2-F 2core
2*0.75 mm^2	H03VVH2-F 2core
1.5 mm^2	CCC 08 (RV-90)
16AWG (1.25 mm^2)	UL1015

Strip the wire insulation to 7 - 9 mm before connecting to the driver terminals. This ensures proper electrical contact and avoids short circuits caused by exposed conductors. Only one wire per terminal.





Expected lifetime

Output current	ta (℃)	30	40	50	55	60	65
350 mA	tc (℃)	51	60	70	74	79	83
	Lifetime	> 100,000 h	> 100,000 h	> 100,000 h	> 95,000 h	> 70,000 h	> 50,000 h

1.The LED driver achieves the above-specified lifetime under reference operating conditions.
2.The correlation between case temperature tc and ambient temperature ta is also affected by luminaire design.

Electrical characteristics

Efficiency vs. Load



Power Factor Characteristics





Operating window



Remarks

- All parameters not specially mentioned are measured at 230 Vac input , full load and 25 ℃ of ambient temperature.
- Ripple & Noise are measured at 20 MHz of bandwidth by using a 300 mm twisted pair-wire terminated with a 0.1 µF & 47 µF parallel capacitor.
- EL compatible with IEC 61347-2-13 Annex J, compatible with EN 60598-2-22 emergency lighting fixtures, compatible with EN 50172 central battery system applications.
- The DC input for this product is only used for emergency lighting and applies to functional and safety requirements，EMC is not considered.
- The driver withstands an input voltage of up to 300 Vac for maximum 1 hour. Shut down of output load might occur in case the supply voltage exceeds the declared input voltage range.
- Shut down of output load happens if the input voltage of the load is below the minimum allowed voltage level.
- Hot plugging of the load or external switching on the secondary side is not permitted.
- Output short circuit protection: If the LED output is short-circuited, the driver shuts down output; normal operation resumes automatically after fault is removed.
- Output over load protection: The driver shuts off the output if the load exceeds the internal preset limit. If the overload persists after restart, the driver shuts down again. Normal operation resumes automatically after the fault is removed.
- Output over voltage protection: If the output voltage exceeds the specified limit, the driver shuts down the output, and automatically returns to normal after the fault is removed.
- Output over temperature protection: The over-temperature protection of the product is provided by the IC. If the temperature exceeds the preset limit, the driver reduces the output current and resumes normal operation after temperature drops.

Packaging information

Item NO.(I/N)	Product name	Weight /piece (kg)	Outer carton dimension (mm)	Quantity /carton	Net weight /Carton (kg)	Gross weight /carton (kg)
61204039	ITS FIX 65/220-240/350 N CS L	0.13	445 x 175 x 165	50	6.75	7.40

Standards

GB 19510.1

GB 19510.213

IEC 61347-1

IEC 61347-2-13

AS/NZS 61347-1

AS/NZS 61347-2-13

EN 62384

GB/T 17743

GB 17625.1

EN 55015

EN 61000-3-2

EN 61000-3-3

EN 61547

EN 61000-4-5

Erp2.0 EU 2019/2020

RoHS (2011/65/EU) (EU)2015/863

Eaglerise is a licensee of the OSRAM brand for
General Lighting LED drivers.
OSRAM is a trademark of OSRAM GmbH.