



CERTIFICATE

No. U6 105345 0004 Rev. 00

Holder of Certificate: **Eaglerise Electric & Electronic (Ji'an) Co., Ltd.**
 Southwest Corner of Panlong Road and Chaoyang Road
 Ji'an Industrial Park
 343100 Ji'an County, Jiangxi Province
 PEOPLE'S REPUBLIC OF CHINA

Certification Mark:



Product: **Electronic controlgear for LED modules (Constant Current LED Power Supply)**

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142260352601

Date, 2026-07-06

(Taylor Yao)



CERTIFICATE

No. U6 105345 0004 Rev. 00

Model(s): ITS DALI-2 15/220-240/350 CS;
ITS DALI-2 20/220-240/500 CS;
ITS DALI-2 30/220-240/700 CS;
ITS DALI-2 42/220-240/1050 CS;
ITS DALI-2 60/220-240/1500 CS;
ITS FIX 20/220-240/500 CS;
ITS FIX 30/220-240/700 CS;
ITS FIX 42/220-240/1050 CS;
ITS FIX 60/220-240/1500 CS

Brand Name: OSRAM

OSRAM

Parameters:

Rated Input Voltage: 220-240VAC or 220-240VAC/DC
Rated Frequency: 50/60Hz or 0/50/60Hz
Rated Input Current: See below table for details
Rated Output: See below table for details
Protection Class: Class II (for ITS DALI-2 15/220-240/350 CS);
Class II (with endcap) (for all other models)
Protection against Electric Shock: SELV
Degree of Protection: IP20 (for ITS DALI-2 15/220-240/350 CS);
IP20 (with endcap) (for all other models)
Method of Installation: Independent (for ITS DALI-2 15/220-240/350 CS);
Independent (with endcap)/ Built-in (without endcap) (for all other models)
Type of Output: Constant current type
ta: See below table for details
tc: See below table for details

Tested according to: EN IEC 61347-2-13:2024
EN IEC 61347-1:2024
EN IEC 62384:2020

Production Facility(ies): 105345

CERTIFICADO



인증서



CERTIFICATO



認証書



CERTIFICATE



认证证书



ZERTIFIKAT

CERTIFICATE

No. U6 105345 0004 Rev. 00

Seri es	Model	Rated Input Current (A)	P _{rated} (W)	Output Voltage (VDC)	I _{rated} (mA)	U _{out} (VDC)	ta (°C)	tc (°C)
1	ITS DALI-2 15/220-240/350 CS	0.11	4.2	9-42	100	60	-20 to +50	80
			5.0		120			
			6.3		150			
			7.6		180			
			8.4		200			
			10.5		250			
			12.6		300			
			14.7		350			
2	ITS DALI-2 20/220-240/500 CS	0.15	6.8	10-45	150	60	-20 to +50	80
			9.0		200			
			11.3		250			
			13.5		300			
			15.8		350			
			18.0		400			
			18.9	10-42	450			
			20.0	10-40	500			
2	ITS DALI-2 30/220-240/700 CS	0.2	15.8	10-45	350	60	-20 to +50	80
			18.0		400			
			20.2		450			
			22.5		500			
			24.8		550			
			27.0		600			
			29.3		650			
			29.4	10-42	700			
3	ITS DALI-2 42/220-240/1050 CS	0.27	31.5	10-45	700	60	-20 to +45 (950-1050mA) -20 to +50 (700-900mA)	85
			33.8		750			
			36.0		800			
			38.3		850			
			40.5		900			
			41.8	10-44	950			
			42.0	10-42	1000			
			42.0	10-40	1050			
4	ITS DALI-2 60/220-240/1500 CS	0.35	38.4	15-48	800	60	-20 to +45 (1200-1500mA) -20 to +50 (800-1050mA)	90
			43.2		900			
			48.0		1000			
			50.4		1050			
			57.6		1200			
			54.6	15-42	1300			
			58.8		1400			
			60.0	15-40	1500			
5	ITS FIX 20/220-240/500 CS	0.2	6.3	23-42	150	59	-20 to +50	80
			8.4		200			
			10.5		250			
			12.6		300			
			14.7		350			
			16.8		400			
			18.9		450			
			20	23-40	500			
5	ITS FIX 30/220-240/700 CS	0.2	14.7	23-42	350	59	-20 to +50	80
			16.8		400			
			18.9		450			
			21.0		500			
			23.1		550			
			25.2		600			
			27.3		650			
			29.4		700			

CERTIFICATE

No. U6 105345 0004 Rev. 00

5	ITS FIX 42/220-240/1050 CS	0.27	29.4	23-42	700	59	-20 to +45 (950-1050mA) -20 to +50 (700-900mA)	85
			31.5		750			
			33.6		800			
			35.7		850			
			37.8		900			
			39.9		950			
			42.0		1000			
			42.0	23-40	1050			
6	ITS FIX 60/220-240/1500 CS	0.37	33.6	24-42	800	59	-20 to +50	85
			37.8		900			
			42.0		1000			
			46.2		1100			
			50.4		1200			
			54.6		1300			
			58.8		1400			
			60.0	24-40	1500			