



# Attestation of Conformity

No. E8A 105345 0005 Rev. 00

**Holder of Attestation:** **Eaglerise Electric & Electronic  
(Ji'an) Co., Ltd.**

Southwest Corner of Panlong Road and Chaoyang Road  
Ji'an Industrial Park  
343100 Ji'an County, Jiangxi Province  
PEOPLE'S REPUBLIC OF CHINA

**Name of Object:** **Electronic controlgear for LED modules  
(Constant Current LED Power Supply)**

This Attestation of Conformity is issued on a voluntary basis according to the Directive 2014/30/EU relating to electromagnetic compatibility. It confirms that the listed apparatus complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 64740260352601

**Date,** 2026-07-03

( Jessie He )

Page 1 of 4

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



# Attestation of Conformity

No. E8A 105345 0005 Rev. 00

**Model(s):**

ITS DALI-2 15/220-240/350 CS;  
ITS DALI-2 20/220-240/500 CS;  
ITS DALI-2 30/220-240/700 CS;  
ITS DALI-2 42/220-240/1050 CS;  
ITS DALI-2 60/220-240/1500 CS;  
ITS FIX 20/220-240/500 CS;  
ITS FIX 30/220-240/700 CS;  
ITS FIX 42/220-240/1050 CS;  
ITS FIX 60/220-240/1500 CS

**Trade name:** OSRAM

# OSRAM

## Description of Object:

Rated Input Voltage: 220-240VAC or 220-240VAC/DC  
Rated Frequency: 50/60Hz or 0/50/60Hz  
Rated Input Current: See below table for details  
Rated Output: See below table for details  
Protection Class: II

**Tested according to:**

EN IEC 55015:2019/A11:2020  
EN IEC 61000-3-2:2019/A2:2024  
EN 61000-3-3:2013/A2:2021  
EN IEC 61547:2023

Page 2 of 4

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.

# Attestation of Conformity

No. E8A 105345 0005 Rev. 00

| Model                         | Rated Input Current (A) | P <sub>rated</sub> (W) | Output Voltage (VDC) | I <sub>rated</sub> (mA) | U <sub>out</sub> (VDC) |
|-------------------------------|-------------------------|------------------------|----------------------|-------------------------|------------------------|
| ITS DALI-2 15/220-240/350 CS  | 0.11                    | 4.2                    | 9-42                 | 100                     | 60                     |
|                               |                         | 5.0                    |                      | 120                     |                        |
|                               |                         | 6.3                    |                      | 150                     |                        |
|                               |                         | 7.6                    |                      | 180                     |                        |
|                               |                         | 8.4                    |                      | 200                     |                        |
|                               |                         | 10.5                   |                      | 250                     |                        |
|                               |                         | 12.6                   |                      | 300                     |                        |
|                               |                         | 14.7                   |                      | 350                     |                        |
| ITS DALI-2 20/220-240/500 CS  | 0.15                    | 6.8                    | 10-45                | 150                     | 60                     |
|                               |                         | 9.0                    |                      | 200                     |                        |
|                               |                         | 11.3                   |                      | 250                     |                        |
|                               |                         | 13.5                   |                      | 300                     |                        |
|                               |                         | 15.8                   |                      | 350                     |                        |
|                               |                         | 18.0                   |                      | 400                     |                        |
|                               |                         | 18.9                   | 10-42                | 450                     |                        |
|                               |                         | 20.0                   | 10-40                | 500                     |                        |
| ITS DALI-2 30/220-240/700 CS  | 0.2                     | 15.8                   | 10-45                | 350                     | 60                     |
|                               |                         | 18.0                   |                      | 400                     |                        |
|                               |                         | 20.2                   |                      | 450                     |                        |
|                               |                         | 22.5                   |                      | 500                     |                        |
|                               |                         | 24.8                   |                      | 550                     |                        |
|                               |                         | 27.0                   |                      | 600                     |                        |
|                               |                         | 29.3                   |                      | 650                     |                        |
|                               |                         | 29.4                   | 10-42                | 700                     |                        |
| ITS DALI-2 42/220-240/1050 CS | 0.27                    | 31.5                   | 10-45                | 700                     | 60                     |
|                               |                         | 33.8                   |                      | 750                     |                        |
|                               |                         | 36.0                   |                      | 800                     |                        |
|                               |                         | 38.3                   |                      | 850                     |                        |
|                               |                         | 40.5                   |                      | 900                     |                        |
|                               |                         | 41.8                   | 10-44                | 950                     |                        |
|                               |                         | 42.0                   | 10-42                | 1000                    |                        |
|                               |                         | 42.0                   | 10-40                | 1050                    |                        |
| ITS DALI-2 60/220-240/1500 CS | 0.35                    | 38.4                   | 15-48                | 800                     | 60                     |
|                               |                         | 43.2                   |                      | 900                     |                        |
|                               |                         | 48.0                   |                      | 1000                    |                        |
|                               |                         | 50.4                   |                      | 1050                    |                        |
|                               |                         | 57.6                   |                      | 1200                    |                        |
|                               |                         | 54.6                   | 15-42                | 1300                    |                        |
|                               |                         | 58.8                   |                      | 1400                    |                        |

Page 3 of 4

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



# Attestation of Conformity

No. E8A 105345 0005 Rev. 00

|                            |      |      |       |      |    |
|----------------------------|------|------|-------|------|----|
|                            |      | 60.0 | 15-40 | 1500 |    |
| ITS FIX 20/220-240/500 CS  | 0.2  | 6.3  | 23-42 | 150  | 59 |
|                            |      | 8.4  |       | 200  |    |
|                            |      | 10.5 |       | 250  |    |
|                            |      | 12.6 |       | 300  |    |
|                            |      | 14.7 |       | 350  |    |
|                            |      | 16.8 |       | 400  |    |
|                            |      | 18.9 |       | 450  |    |
|                            |      | 20   | 23-40 | 500  |    |
| ITS FIX 30/220-240/700 CS  | 0.2  | 14.7 | 23-42 | 350  | 59 |
|                            |      | 16.8 |       | 400  |    |
|                            |      | 18.9 |       | 450  |    |
|                            |      | 21.0 |       | 500  |    |
|                            |      | 23.1 |       | 550  |    |
|                            |      | 25.2 |       | 600  |    |
|                            |      | 27.3 |       | 650  |    |
|                            |      | 29.4 |       | 700  |    |
| ITS FIX 42/220-240/1050 CS | 0.27 | 29.4 | 23-42 | 700  | 59 |
|                            |      | 31.5 |       | 750  |    |
|                            |      | 33.6 |       | 800  |    |
|                            |      | 35.7 |       | 850  |    |
|                            |      | 37.8 |       | 900  |    |
|                            |      | 39.9 |       | 950  |    |
|                            |      | 42.0 |       | 1000 |    |
|                            |      | 42.0 | 23-40 | 1050 |    |
| ITS FIX 60/220-240/1500 CS | 0.37 | 33.6 | 24-42 | 800  | 59 |
|                            |      | 37.8 |       | 900  |    |
|                            |      | 42.0 |       | 1000 |    |
|                            |      | 46.2 |       | 1100 |    |
|                            |      | 50.4 |       | 1200 |    |
|                            |      | 54.6 |       | 1300 |    |
|                            |      | 58.8 |       | 1400 |    |
|                            |      | 60.0 | 24-40 | 1500 |    |

Page 4 of 4

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.