



# Licence for



## CENELEC ENEC Agreement Licence Ref. No. SE/19019-7


<b>Product:</b>	<b>a.c. supplied electronic controlgear for LED modules (LED POWER SUPPLY)</b>
<b>Type designation:</b>	CH-25-*** IP65 LB1
<b>Test Report No.</b>	190424160GZU-001
<b>Licence holder:</b>	Eaglerise Electric & Electronic (China) Co., Ltd. A3 Guicheng Science & Technology Park, Jianping Road, Nanhai, Foshan, Guangdong, 528200 China
<b>The product complies with the standard(s):</b>	EN 61347-1:2015 EN 61347-2-13:2014+A1
<b>Licence holder is authorized to use the mark with the following limitations:</b>	-
<b>Date of expiry:</b>	1 July 2024
<b>EU Directive information:</b>	According to the principle of presumption of conformity, this certificate constitutes support for an EC Declaration of Conformity and CE marking according to the Low Voltage Directive 2014/35/EU.

### Additional information in Appendix

<i>Certification Body</i>	Intertek Semko AB, Product Certification	<i>Place</i>	Kista - Stockholm
<i>Signed</i>	 Henrik Wikström	<i>Date</i>	1 July 2019
<i>Internal reference:</i>	ASF		<i>Page 1 of 3</i>

This Licence is the result of testing a sample of the product submitted, in accordance with the provisions of the relevant specific standard. A copy of the Licence shall be filed in the place of manufacturing. The Licence has been established by a body which is a signatory to the ENEC Agreement ratified by CENELEC Marks Committee on 10 April 1992.

**APPENDIX****CENELEC ENEC Agreement Licence Ref. No. SE/19019-7****Test Report No.** 190424160GZU-001**Technical data**

*Type designation* CH-25-\*\*\* IP65 LB1  
*Input* 100-240 Vac; 50/60 Hz; 0,38 A;  $\lambda \geq 0,95$ ;  
*Output* Constant current type;  
*Brand name:*   
*Product information* Output: SELV; Double insulation; ta 50 °C; tc 85 °C;  
Built-in type;  
110 °C thermal protection; Inherently short-circuit  
proof;  
Suitable for direct mounting on normally flammable  
surfaces.  
Other information see Additional information Model list.

The product has also been checked according to  
EN 62384: 2006 + A1

**Manufacturing site(s):** Eaglerise Electric & Electronic (China) Co.,Ltd. Beijiao Branch  
No. 4, East Huanzhen Road, Beijiao, Shunde, Foshan,  
Guangdong 528000, China

According to the principle of presumption of conformity, this certificate, which includes production control, constitutes support for an EC Declaration of Conformity and CE marking according to the Low Voltage Directive 2014/35/EU.

This presumption can expire before end of validity of this certificate due to new issued Standard or Amendment and changes within the EU legislation.

The instruction for use shall be written in a language acceptable according to the national regulation in the country where the product is to be used.

*Certification Body* Intertek Semko AB, Product Certification *Place* Kista - Stockholm

*Signed*   
Henrik Wikström *Date* 1 July 2019

## APPENDIX

### CENELEC ENEC Agreement Licence Ref. No. SE/19019-7

#### Additional information :

Explanation for Type designation CH-25-\*\*\* IP65 LB1: "\*\*\*\*" is for the output current and represents the number from 300 to 800 increasing in step of 50, for example, 300 means the output current is 300 mA.

Model List:

No.	Model number	Input			Output			
		Voltage (VAC)	Max. Current (A)	Frequency (Hz)	Constant current	Normal working voltage	No load working	Max. Power (W) Max.
1	CH-25-300 IP65 LB1	100-240	0.38	50/60	300	50-84	98	25.2
2	CH-25-350 IP65 LB1	100-240	0.38	50/60	350	43-72	85	25.2
3	CH-25-400 IP65 LB1	100-240	0.38	50/60	400	37.5-63	75	25.2
4	CH-25-450 IP65 LB1	100-240	0.38	50/60	450	33.5-56	68	25.2
5	CH-25-500 IP65 LB1	100-240	0.38	50/60	500	30-50	63	25
6	CH-25-550 IP65 LB1	100-240	0.38	50/60	550	27-45.5	55	25
7	CH-25-600 IP65 LB1	100-240	0.38	50/60	600	25-42	50	25.2
8	CH-25-650 IP65 LB1	100-240	0.38	50/60	650	23-38.5	50	25
9	CH-25-700 IP65 LB1	100-240	0.38	50/60	700	21.5-36	46	25.2
10	CH-25-750 IP65 LB1	100-240	0.38	50/60	750	20-33.5	44	25.1
11	CH-25-800 IP65 LB1	100-240	0.38	50/60	800	19-31.5	42	25.2

