

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

LED Power Supply

Name and address of the applicant

Foshan Eaglerise Power Science & Technology (Shunde)
Co., Ltd.
No.4, East Huanzhen Road, Beijiao Shunde
Foshan Guangdong
China

Name and address of the manufacturer

Foshan Eaglerise Power Science & Technology (Shunde)
Co., Ltd.
No.4, East Huanzhen Road, Beijiao Shunde
Foshan Guangdong
China

Name and address of the factory

Note: When more than one factory, please report on page 2

 Additional information on page 2

Ratings and principal characteristics

PRI: LV supply: max. 0.32 A, 220-240 V~, 50/60 Hz, Cl. II

Trademark (if any)



Type of Manufacturer's Testing Laboratories used

Model / Type Ref.

FLS-15-350 0-10 LA, FLS-25-600 0-10 LA, FLS-44-1050 0-10 LA

Additional information (if necessary may also be reported on page 2)

 Additional information on page 2

A sample of the product was tested and found to be in conformity with

IEC 61347-2-13:2014, IEC 61347-2-13:2014/AMD1:2016
IEC 61347-1:2015, IEC 61347-1:2015/AMD1:2017

As shown in the Test Report Ref. No. which forms part of this Certificate

481058

This CB Test Certificate is issued by the National Certification Body



Philip Pedersens vei 11,
NO-1366 Lysaker, Norway

Date: 13-09-2022



Signature: Juan Z. Saussey
Certification Department

Foshan Eaglerise Power Science & Technology (Shunde)
Co., Ltd.
No.4, East Huanzhen Road, Beijiao Shunde
Foshan Guangdong
China

EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO.,
LTD
West Zone, Ji An County Industrial Park, Ji an County
Jiangxi Province
China

Additional information(if necessary)

PF: 0.4C-0.95 for model FLS-15-350 0-10 LA, PF: 0.4C-0.95 for model FLS-25-600 0-10 LA, PF: 0.6C-0.97 for model FLS-44-1050 0-10 LA. SEC: FLS-15-350 0-10 LA: Max. 14.7 W, 0.12-0.35 A, 9-42 Vd.c. (under load), max. 59 Vd.c. (no-load); FLS-25-600 0-10 LA: Max. 25.2 W, 0.2-0.6 A, 9-42 Vd.c. (under load), max. 59 Vd.c. (no-load); FLS-44-1050 0-10 LA: Max. 44.1 W, 0.65-1.05 A, 9-42 Vd.c. (under load), max. 59 Vd.c. (no-load). Independent type; SELV, constant current output, thermal protected 110°C, ta: 45°C, tc: 85°C



Philip Pedersens vei 11,
NO-1366 Lysaker, Norway

Date: 13-09-2022



Signature: Juan Z. Saussey
Certification Department