

Certificate of Conformity

Global-Mark Pty. Ltd., certify the electrical equipment described hereunder complies with standards listed herein and notifies the certificate holder to affix the authorised Approval Mark on the product of the same type and the Regulatory Compliance Mark (RCM) mark provided that the requirements of all relevant parts of AS/NZS 4417 applicable to the article are fulfilled. In placing the Approval and RCM mark on the product, the Responsible Supplier makes a declaration of compliance with the certification standard(s) and confirms that the product is identical to the product certified herein. – This Certificate meets the requirements of a Recognised External Certification Scheme (EESS- RECS) and a Recognised External Approval Scheme (NSW-REAS).

CERTIFICATION AND CERTIFICATE HOLDER DETAILS

Company Name	Foshan Eaglerise Power Science & Technology (Shunde) Co.,Ltd	Other Name	
Address	No 4 East Huanzhen Road, Beijiao Shunde, Foshan Guangdong 528000 China		
Client ID	107687	Global-Mark File Number:	107687-035
Certificate Number & Approval Mark	GMA-514349-EA	Revision Number	00
Certification Standard(s)	AS 61347.2.13:2018 & AS/NZS 61347.1:2016 + A1 Lamp Control Gear - Part 2-13: Particular Requirements For D.C Or A.C Supplied Electronic Control Gear For Led Modules.		
Type of Certification	Electrical Safety Product	Scheme	Global-Mark Electrical Product Safety Certification Scheme
			System 1 Approval

CERTIFICATE DATES

Certificate Issue Date	20/12/2022
Certificate Last Update Date	
Certification Expiry Date	20/12/2027

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Certificate of Conformity

CERTIFIED ELECTRICAL EQUIPMENT				
Declared Article	Product Description	Trade Name	Model Number	Rating
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-150 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 150mA,5-12Vdc, 24Vdc max, 1.8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-150 SI E	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 150mA,5-12Vdc, 24Vdc max, 1.8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-200 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 200mA,5-12Vdc, 24Vdc max, 2.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-200 SI E	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 200mA,5-12Vdc, 24Vdc max, 2.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-250 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 250mA,5-12Vdc, 24Vdc max, 3W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-250 SI E	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 250mA,5-12Vdc, 24Vdc max, 3W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-300 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 300mA,5-12Vdc, 24Vdc max, 3.6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-300 SI E	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 300mA,5-12Vdc, 24Vdc max, 3.6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-350 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 350mA,5-12Vdc, 24Vdc max, 4.2W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-350 SI E	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 350mA,5-12Vdc, 24Vdc max, 4.2W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-400 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 400mA,2.5-4.5Vdc, 16Vdc max, 1.8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-400 SI E	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 400mA,2.5-4.5Vdc, 16Vdc max, 1.8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-450 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 450mA,2.5-4.5Vdc, 16Vdc max, 2.03W max.

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager




Certificate of Conformity

Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-450 SI E	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 450mA,2.5-4.5Vdc, 16Vdc max, 2.03W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-500 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 500mA,2.5-4.5Vdc, 16Vdc max, 2.25W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-500 SI E	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 500mA,2.5-4.5Vdc, 16Vdc max, 2.25W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-550 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 550mA,2.5-4.5Vdc, 16Vdc max, 2.48W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-550 SI E	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 550mA,2.5-4.5Vdc, 16Vdc max, 2.48W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-600 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 600mA,2.5-4.5Vdc, 16Vdc max, 2.7W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-600 SI E	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 600mA,2.5-4.5Vdc, 16Vdc max, 2.7W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-650 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 650mA,2.5-4.5Vdc, 10Vdc max, 2.9W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-650 SI E	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 650mA,2.5-4.5Vdc, 10Vdc max, 2.9W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-700 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 700mA,2.5-4.5Vdc, 10Vdc max, 3.15W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-3-700 SI E	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.45; Output: 700mA,2.5-4.5Vdc, 10Vdc max, 3.15W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-120 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 120mA,27-40Vdc, 59Vdc max, 4.8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-120 SI E	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 120mA,27-40Vdc, 59Vdc max, 4.8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-150 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 150mA,27-40Vdc, 59Vdc max, 6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-150 SI E	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 150mA,27-40Vdc, 59Vdc max, 6W max.

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager




Certificate of Conformity

Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-180 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 180mA,27-40Vdc, 59Vdc max, 7.2W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-180 SI E	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 180mA,27-40Vdc, 59Vdc max, 7.2W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-200 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 200mA,27-40Vdc, 59Vdc max, 8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-200 SI E	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 200mA,27-40Vdc, 59Vdc max, 8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-220 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 220mA,27-40Vdc, 59Vdc max, 8.8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-220 SI E	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 220mA,27-40Vdc, 59Vdc max, 8.8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-250 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 250mA,10-24Vdc, 45Vdc max, 6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-250 SI E	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 250mA,10-24Vdc, 45Vdc max, 6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-300 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 300mA,8-20Vdc, 40Vdc max, 6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-300 SI E	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 300mA,8-20Vdc, 40Vdc max, 6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-350 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 350mA,8-18Vdc, 40Vdc max, 6.3W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-350 SI E	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 350mA,8-18Vdc, 40Vdc max, 6.3W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-400 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 400mA,5-15Vdc, 30Vdc max, 6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-400 SI E	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 400mA,5-15Vdc, 30Vdc max, 6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-450 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 450mA,5-13.5Vdc, 30Vdc max, 6.1W max.

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Certificate of Conformity

Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-450 SI E	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 450mA,5-13.5Vdc, 30Vdc max, 6.1W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-500 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 500mA,5-12Vdc, 30Vdc max, 6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-500 SI E	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 500mA,5-12Vdc, 30Vdc max, 6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-550 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 550mA,5-11Vdc, 30Vdc max, 6.05W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-550 SI E	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 550mA,5-11Vdc, 30Vdc max, 6.05W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-600 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 600mA,4-9Vdc, 25Vdc max, 5.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-600 SI E	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 600mA,4-9Vdc, 25Vdc max, 5.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-650 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 650mA,4-9Vdc, 25Vdc max, 5.85W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-650 SI E	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 650mA,4-9Vdc, 25Vdc max, 5.85W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-700 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 700mA,4-9Vdc, 25Vdc max, 6.3W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-6-700 SI E	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5; Output: 700mA,4-9Vdc, 25Vdc max, 6.3W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-120 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.8C-0.95; Output: 120mA,27-50Vdc, 59Vdc max, 6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-150 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.8C-0.95; Output: 150mA,27-50Vdc, 59Vdc max, 7.5W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-180 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.8C-0.95; Output: 180mA,22-42Vdc, 55Vdc max, 7.6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-200 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.8C-0.95; Output: 200mA,22-42Vdc, 55Vdc max, 8.4W max.

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Certificate of Conformity

Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-220 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.8C-0.95; Output: 220mA,22-42Vdc, 55Vdc max, 9.24W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-250 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.8C-0.95; Output: 250mA,14-27Vdc, 45Vdc max, 6.75W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-300 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.8C-0.95; Output: 300mA,14-27Vdc, 45Vdc max, 8.1W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-350 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.8C-0.95; Output: 350mA,12-24Vdc, 35Vdc max, 8.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-12-250 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.09A max., λ :0.75C-0.95; Output: 250mA,24-42Vdc, 55Vdc max, 10.5W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-12-300 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.09A max., λ :0.75C-0.95; Output: 300mA,24-42Vdc, 55Vdc max, 12.6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-12-350 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.09A max., λ :0.75C-0.95; Output: 350mA,24-40Vdc, 55Vdc max, 14W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-20-350 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.16A max., λ :0.9C-0.95; Output: 350mA,40-60Vdc, 75Vdc max, 21W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-20-400 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.16A max., λ :0.9C-0.95; Output: 400mA,24-42Vdc, 55Vdc max, 16.8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-20-450 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.16A max., λ :0.9C-0.95; Output: 450mA,24-42Vdc, 55Vdc max, 18.9W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-20-500 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.16A max., λ :0.9C-0.95; Output: 500mA,24-42Vdc, 55Vdc max, 21W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-20-550 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.16A max., λ :0.9C-0.95; Output: 550mA,24-40Vdc, 55Vdc max, 22W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-20-600 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.16A max., λ :0.9C-0.95; Output: 600mA,24-40Vdc, 55Vdc max, 24W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-20-700 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.16A max., λ :0.9C-0.95; Output: 700mA,18-30Vdc, 45Vdc max, 21W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-120 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.8C-0.95; Output: 120mA,27-50Vdc, 59Vdc max, 6W max.

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager

Certificate of Conformity

Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-150 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.8C-0.95; Output: 150mA,27-50Vdc, 59Vdc max., 7.5W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-180 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.8C-0.95; Output: 180mA,22-42Vdc, 55Vdc max., 7.6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-200 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.8C-0.95; Output: 200mA,22-42Vdc, 55Vdc max., 8.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-220 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.8C-0.95; Output: 220mA,22-42Vdc, 55Vdc max., 9.24W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-250 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.8C-0.95; Output: 250mA,14-27Vdc, 45Vdc max., 6.75W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-300 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.8C-0.95; Output: 300mA,14-27Vdc, 45Vdc max., 8.1W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-350 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.8C-0.95; Output: 350mA,12-24Vdc, 35Vdc max., 8.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-12-250 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.09A max., λ :0.75C-0.95; Output: 250mA,24-42Vdc, 55Vdc max., 10.5W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-12-300 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.09A max., λ :0.75C-0.95; Output: 300mA,24-42Vdc, 55Vdc max., 12.6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-12-350 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.09A max., λ :0.75C-0.95; Output: 350mA,24-40Vdc, 55Vdc max., 14W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-20-350 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.16A max., λ :0.9C-0.95; Output: 350mA,40-60Vdc, 75Vdc max., 21W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-20-400 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.16A max., λ :0.9C-0.95; Output: 400mA,24-42Vdc, 55Vdc max., 16.8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-20-450 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.16A max., λ :0.9C-0.95; Output: 450mA,24-42Vdc, 55Vdc max., 18.9W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-20-500 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.16A max., λ :0.9C-0.95; Output: 500mA,24-42Vdc, 55Vdc max., 21W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-20-550 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.16A max., λ :0.9C-0.95; Output: 550mA,24-40Vdc, 55Vdc max., 22W max.

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Certificate of Conformity

Power Supply or Charger	LED Power Supply	EAGLERISE	LS-20-600 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.16A max., λ :0.9C-0.95; Output: 600mA,24-40Vdc, 55Vdc max, 24W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-20-700 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.16A max., λ :0.9C-0.95; Output: 700mA,18-30Vdc, 45Vdc max, 21W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-21-300 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.3A max., λ :0.55C; Output: 300mA,50-70Vdc, 90Vdc max, 21W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-21-300 SI E	Input: 220-240 V~, 50/60 Hz, 0.3A max., λ :0.55C; Output: 300mA,50-70Vdc, 90Vdc max, 21W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-21-350 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.3A max., λ :0.55C; Output: 350mA,42-60Vdc, 80Vdc max, 21W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-21-350 SI E	Input: 220-240 V~, 50/60 Hz, 0.3A max., λ :0.55C; Output: 350mA,42-60Vdc, 80Vdc max, 21W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-21-400 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.3A max., λ :0.55C; Output: 400mA,27-42Vdc, 55Vdc max, 16.8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-21-400 SI E	Input: 220-240 V~, 50/60 Hz, 0.3A max., λ :0.55C; Output: 400mA,27-42Vdc, 55Vdc max, 16.8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-21-450 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.3A max., λ :0.55C; Output: 450mA,27-42Vdc, 55Vdc max, 18.9W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-21-450 SI E	Input: 220-240 V~, 50/60 Hz, 0.3A max., λ :0.55C; Output: 450mA,27-42Vdc, 55Vdc max, 18.9W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-21-500 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.3A max., λ :0.55C; Output: 500mA,27-42Vdc, 55Vdc max, 21W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-21-500 SI E	Input: 220-240 V~, 50/60 Hz, 0.3A max., λ :0.55C; Output: 500mA,27-42Vdc, 55Vdc max, 21W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-21-550 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.3A max., λ :0.55C; Output: 550mA,27-40Vdc, 55Vdc max, 22W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-21-550 SI E	Input: 220-240 V~, 50/60 Hz, 0.3A max., λ :0.55C; Output: 550mA,27-40Vdc, 55Vdc max, 22W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-21-600 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.3A max., λ :0.55C; Output: 600mA,27-39Vdc, 55Vdc max, 23.4W max.

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager





global-mark®

Certificate of Conformity

Power Supply or Charger	LED Power Supply	EAGLERISE	LS-21-600 SI E	Input: 220-240 V~, 50/60 Hz, 0.3A max., λ :0.55C; Output: 600mA,27-39Vdc, 55Vdc max, 23.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-21-650 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.3A max., λ :0.55C; Output: 650mA,20-32Vdc, 50Vdc max, 20.8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-21-650 SI E	Input: 220-240 V~, 50/60 Hz, 0.3A max., λ :0.55C; Output: 650mA,20-32Vdc, 50Vdc max, 20.8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-21-700 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.3A max., λ :0.55C; Output: 700mA,18-30Vdc, 50Vdc max, 21W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-21-700 SI E	Input: 220-240 V~, 50/60 Hz, 0.3A max., λ :0.55C; Output: 700mA,18-30Vdc, 50Vdc max, 21W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-120 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.08A max., λ :0.5C; Output: 120mA,30-42Vdc, 59Vdc max, 5.1W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-120 SI E	Input: 220-240 V~, 50/60 Hz, 0.08A max., λ :0.5C; Output: 120mA,30-42Vdc, 59Vdc max, 5.1W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-150 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.09A max., λ :0.5C; Output: 150mA,30-42Vdc, 59Vdc max, 6.3W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-150 SI E	Input: 220-240 V~, 50/60 Hz, 0.09A max., λ :0.5C; Output: 150mA,30-42Vdc, 59Vdc max, 6.3W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-180 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5C; Output: 180mA,30-42Vdc, 59Vdc max, 7.6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-180 SI E	Input: 220-240 V~, 50/60 Hz, 0.11A max., λ :0.5C; Output: 180mA,30-42Vdc, 59Vdc max, 7.6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-200 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.12A max., λ :0.5C; Output: 200mA,30-42Vdc, 59Vdc max, 8.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-200 SI E	Input: 220-240 V~, 50/60 Hz, 0.12A max., λ :0.5C; Output: 200mA,30-42Vdc, 59Vdc max, 8.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-220 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.5C; Output: 220mA, 30-38.5Vdc, 50Vdc max, 8.5W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-220 SI E	Input: 220-240 V~, 50/60 Hz, 0.07A max., λ :0.5C; Output: 220mA, 30-38.5Vdc, 50Vdc max, 8.5W max.

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Certificate of Conformity

Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-250 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.1A max., λ :0.5C; Output: 250mA,16-26Vdc, 37Vdc max, 6.5W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-250 SI E	Input: 220-240 V~, 50/60 Hz, 0.1A max., λ :0.5C; Output: 250mA,16-26Vdc, 37Vdc max, 6.5W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-300 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.1A max., λ :0.5C; Output: 300mA,15-24Vdc, 40Vdc max, 7.2W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-300 SI E	Input: 220-240 V~, 50/60 Hz, 0.1A max., λ :0.5C; Output: 300mA,15-24Vdc, 40Vdc max, 7.2W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-350 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.12A max., λ :0.5C; Output: 350mA,15-24Vdc, 35Vdc max, 8.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-350 SI E	Input: 220-240 V~, 50/60 Hz, 0.12A max., λ :0.5C; Output: 350mA,15-24Vdc, 35Vdc max, 8.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-400 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.12A max., λ :0.5C; Output: 400mA,12-20Vdc, 30Vdc max, 8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-400 SI E	Input: 220-240 V~, 50/60 Hz, 0.12A max., λ :0.5C; Output: 400mA,12-20Vdc, 30Vdc max, 8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-450 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.12A max., λ :0.5C; Output: 450mA,11-18Vdc, 30Vdc max, 8.1W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-450 SI E	Input: 220-240 V~, 50/60 Hz, 0.12A max., λ :0.5C; Output: 450mA,11-18Vdc, 30Vdc max, 8.1W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-500 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.12A max., λ :0.5C; Output: 500mA,10-16Vdc, 26Vdc max, 8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-500 SI E	Input: 220-240 V~, 50/60 Hz, 0.12A max., λ :0.5C; Output: 500mA,10-16Vdc, 26Vdc max, 8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-550 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.12A max., λ :0.5C; Output: 550mA,9-14Vdc, 25Vdc max, 7.7W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-550 SI E	Input: 220-240 V~, 50/60 Hz, 0.12A max., λ :0.5C; Output: 550mA,9-14Vdc, 25Vdc max, 7.7W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-600 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.12A max., λ :0.5C; Output: 600mA,8-13Vdc, 25Vdc max, 7.8W max.

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Certificate of Conformity

Power Supply or Charger	LED Power Supply	EAGLERISE	LS-8-600 SI E	Input: 220-240 V~, 50/60 Hz, 0.12A max., λ :0.55C; Output: 600mA,8-13Vdc, 25Vdc max, 7.8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-12-250 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.15A max., λ :0.55C; Output: 250mA,30-42Vdc, 59Vdc max, 10.5W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-12-250 SI E	Input: 220-240 V~, 50/60 Hz, 0.15A max., λ :0.55C; Output: 250mA,30-42Vdc, 59Vdc max, 10.5W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-12-300 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.18A max., λ :0.55C; Output: 300mA,30-42Vdc, 59Vdc max, 12.6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-12-300 SI E	Input: 220-240 V~, 50/60 Hz, 0.18A max., λ :0.55C; Output: 300mA,30-42Vdc, 59Vdc max, 12.6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-12-350 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.2A max., λ :0.55C; Output: 350mA,27-40Vdc, 57Vdc max, 14W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-12-350 SI E	Input: 220-240 V~, 50/60 Hz, 0.2A max., λ :0.55C; Output: 350mA,27-40Vdc, 57Vdc max, 14W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-12-400 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.18A max., λ :0.55C; Output: 400mA,20-30Vdc, 45Vdc max, 12W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-12-400 SI E	Input: 220-240 V~, 50/60 Hz, 0.18A max., λ :0.55C; Output: 400mA,20-30Vdc, 45Vdc max, 12W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-12-450 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.18A max., λ :0.55C; Output: 450mA,16-26Vdc, 39Vdc max, 11.7W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-12-450 SI E	Input: 220-240 V~, 50/60 Hz, 0.18A max., λ :0.55C; Output: 450mA,16-26Vdc, 39Vdc max, 11.7W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-12-500 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.19A max., λ :0.55C; Output: 500mA,14-26Vdc, 39Vdc max, 13W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-12-500 SI E	Input: 220-240 V~, 50/60 Hz, 0.19A max., λ :0.55C; Output: 500mA,14-26Vdc, 39Vdc max, 13W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-12-550 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.19A max., λ :0.55C; Output: 550mA,12-21Vdc, 32Vdc max, 11.6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-12-550 SI E	Input: 220-240 V~, 50/60 Hz, 0.19A max., λ :0.55C; Output: 550mA,12-21Vdc, 32Vdc max, 11.6W max.

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager




Certificate of Conformity

Power Supply or Charger	LED Power Supply	EAGLERISE	LS-12-600 SI ECO	Input: 220-240 V~, 50/60 Hz, 0.19A max., λ :0.55C; Output: 600mA,11-20Vdc, 31Vdc max, 12W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-12-600 SI E	Input: 220-240 V~, 50/60 Hz, 0.19A max., λ :0.55C; Output: 600mA,11-20Vdc, 31Vdc max, 12W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-600 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.17A max., λ :0.95; Output: 600mA,24-42Vdc, 50Vdc max, 25.2W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-600 LI ECO-1	Input: 220-240 V~, 50/60 Hz, 0.17A max., λ :0.95; Output: 600mA,24-42Vdc, 50Vdc max, 25.2W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-650 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.19A max., λ :0.95; Output: 650mA,24-42Vdc, 50Vdc max, 27.3W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-650 LI ECO-1	Input: 220-240 V~, 50/60 Hz, 0.19A max., λ :0.95; Output: 650mA,24-42Vdc, 50Vdc max, 27.3W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-700 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.2A max., λ :0.95; Output: 700mA,24-42Vdc, 50Vdc max, 29.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-700 LI ECO-1	Input: 220-240 V~, 50/60 Hz, 0.2A max., λ :0.95; Output: 700mA,24-42Vdc, 50Vdc max, 29.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-750 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.22A max., λ :0.95; Output: 750mA,24-42Vdc, 50Vdc max, 31.5W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-750 LI ECO-1	Input: 220-240 V~, 50/60 Hz, 0.22A max., λ :0.95; Output: 750mA,24-42Vdc, 50Vdc max, 31.5W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-800 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.23A max., λ :0.95; Output: 800mA,24-42Vdc, 50Vdc max, 33.6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-800 LI ECO-1	Input: 220-240 V~, 50/60 Hz, 0.23A max., λ :0.95; Output: 800mA,24-42Vdc, 50Vdc max, 33.6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-850 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.25A max., λ :0.95; Output: 850mA,24-42Vdc, 50Vdc max, 35.7W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-850 LI ECO-1	Input: 220-240 V~, 50/60 Hz, 0.25A max., λ :0.95; Output: 850mA,24-42Vdc, 50Vdc max, 35.7W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-900 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.26A max., λ :0.95; Output: 900mA,24-42Vdc, 50Vdc max, 37.8W max.

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager




Certificate of Conformity

Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-900 LI ECO-1	Input: 220-240 V~, 50/60 Hz, 0.26A max., λ :0.95; Output: 900mA,24-42Vdc, 50Vdc max, 37.8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-950 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.27A max., λ :0.95; Output: 950mA,24-42Vdc, 50Vdc max, 39.9W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-950 LI ECO-1	Input: 220-240 V~, 50/60 Hz, 0.27A max., λ :0.95; Output: 950mA,24-42Vdc, 50Vdc max, 39.9W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-1000 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.27A max., λ :0.95; Output: 1000mA,24-40Vdc, 50Vdc max, 40W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-1000 LI ECO-1	Input: 220-240 V~, 50/60 Hz, 0.27A max., λ :0.95; Output: 1000mA,24-40Vdc, 50Vdc max, 40W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-1050 LI ECO	Input: 220-240 V~, 50/60 Hz, 0.29A max., λ :0.95; Output: 1050mA,24-38.5Vdc, 52Vdc max, 40.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-1050 LI ECO-1	Input: 220-240 V~, 50/60 Hz, 0.29A max., λ :0.95; Output: 1050mA,24-38.5Vdc, 52Vdc max, 40.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-600 LI-G ECO	Input: 220-240 V~, 50/60 Hz, 0.17A max., λ :0.95; Output: 600mA,24-42Vdc, 50Vdc max, 25.2W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-600 LI-G ECO-1	Input: 220-240 V~, 50/60 Hz, 0.17A max., λ :0.95; Output: 600mA,24-42Vdc, 50Vdc max, 25.2W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-650 LI-G ECO	Input: 220-240 V~, 50/60 Hz, 0.19A max., λ :0.95; Output: 650mA,24-42Vdc, 50Vdc max, 27.3W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-650 LI-G ECO-1	Input: 220-240 V~, 50/60 Hz, 0.19A max., λ :0.95; Output: 650mA,24-42Vdc, 50Vdc max, 27.3W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-700 LI-G ECO	Input: 220-240 V~, 50/60 Hz, 0.2A max., λ :0.95; Output: 700mA,24-42Vdc, 50Vdc max, 29.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-700 LI-G ECO-1	Input: 220-240 V~, 50/60 Hz, 0.2A max., λ :0.95; Output: 700mA,24-42Vdc, 50Vdc max, 29.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-750 LI-G ECO	Input: 220-240 V~, 50/60 Hz, 0.22A max., λ :0.95; Output: 750mA,24-42Vdc, 50Vdc max, 31.5W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-750 LI-G ECO-1	Input: 220-240 V~, 50/60 Hz, 0.22A max., λ :0.95; Output: 750mA,24-42Vdc, 50Vdc max, 31.5W max.

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager




Certificate of Conformity

Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-800 LI-G ECO	Input: 220-240 V~, 50/60 Hz, 0.23A max., λ :0.95; Output: 800mA,24-42Vdc, 50Vdc max, 33.6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-800 LI-G ECO-1	Input: 220-240 V~, 50/60 Hz, 0.23A max., λ :0.95; Output: 800mA,24-42Vdc, 50Vdc max, 33.6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-850 LI-G ECO	Input: 220-240 V~, 50/60 Hz, 0.25A max., λ :0.95; Output: 850mA,24-42Vdc, 50Vdc max, 35.7W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-850 LI-G ECO-1	Input: 220-240 V~, 50/60 Hz, 0.25A max., λ :0.95; Output: 850mA,24-42Vdc, 50Vdc max, 35.7W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-900 LI-G ECO	Input: 220-240 V~, 50/60 Hz, 0.26A max., λ :0.95; Output: 900mA,24-42Vdc, 50Vdc max, 37.8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-900 LI-G ECO-1	Input: 220-240 V~, 50/60 Hz, 0.26A max., λ :0.95; Output: 900mA,24-42Vdc, 50Vdc max, 37.8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-950 LI-G ECO	Input: 220-240 V~, 50/60 Hz, 0.27A max., λ :0.95; Output: 950mA,24-42Vdc, 50Vdc max, 39.9W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-950 LI-G ECO-1	Input: 220-240 V~, 50/60 Hz, 0.27A max., λ :0.95; Output: 950mA,24-42Vdc, 50Vdc max, 39.9W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-1000 LI-G ECO	Input: 220-240 V~, 50/60 Hz, 0.27A max., λ :0.95; Output: 1000mA,24-40Vdc, 50Vdc max, 40W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-1000 LI-G ECO-1	Input: 220-240 V~, 50/60 Hz, 0.27A max., λ :0.95; Output: 1000mA,24-40Vdc, 50Vdc max, 40W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-1050 LI-G ECO	Input: 220-240 V~, 50/60 Hz, 0.29A max., λ :0.95; Output: 1050mA,24-38.5Vdc, 52Vdc max, 40.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-1050 LI-G ECO-1	Input: 220-240 V~, 50/60 Hz, 0.29A max., λ :0.95; Output: 1050mA,24-38.5Vdc, 52Vdc max, 40.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-600 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.17A max., λ :0.95; Output: 600mA,24-42Vdc, 50Vdc max, 25.2W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-600 LI EXC-1	Input: 220-240 V~, 50/60 Hz, 0.17A max., λ :0.95; Output: 600mA,24-42Vdc, 50Vdc max, 25.2W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-650 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.19A max., λ :0.95; Output: 650mA,24-42Vdc, 50Vdc max, 27.3W max.

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Certificate of Conformity

Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-650 LI EXC-1	Input: 220-240 V~, 50/60 Hz, 0.19A max., λ :0.95; Output: 650mA,24-42Vdc, 50Vdc max, 27.3W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-700 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.2A max., λ :0.95; Output: 700mA,24-42Vdc, 50Vdc max, 29.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-700 LI EXC-1	Input: 220-240 V~, 50/60 Hz, 0.2A max., λ :0.95; Output: 700mA,24-42Vdc, 50Vdc max, 29.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-750 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.22A max., λ :0.95; Output: 750mA,24-42Vdc, 50Vdc max, 31.5W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-750 LI EXC-1	Input: 220-240 V~, 50/60 Hz, 0.22A max., λ :0.95; Output: 750mA,24-42Vdc, 50Vdc max, 31.5W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-800 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.23A max., λ :0.95; Output: 800mA,24-42Vdc, 50Vdc max, 33.6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-800 LI EXC-1	Input: 220-240 V~, 50/60 Hz, 0.23A max., λ :0.95; Output: 800mA,24-42Vdc, 50Vdc max, 33.6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-850 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.25A max., λ :0.95; Output: 850mA,24-42Vdc, 50Vdc max, 35.7W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-850 LI EXC-1	Input: 220-240 V~, 50/60 Hz, 0.25A max., λ :0.95; Output: 850mA,24-42Vdc, 50Vdc max, 35.7W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-900 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.26A max., λ :0.95; Output: 900mA,24-42Vdc, 50Vdc max, 37.8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-900 LI EXC-1	Input: 220-240 V~, 50/60 Hz, 0.26A max., λ :0.95; Output: 900mA,24-42Vdc, 50Vdc max, 37.8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-950 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.27A max., λ :0.95; Output: 950mA,24-42Vdc, 50Vdc max, 39.9W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-950 LI EXC-1	Input: 220-240 V~, 50/60 Hz, 0.27A max., λ :0.95; Output: 950mA,24-42Vdc, 50Vdc max, 39.9W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-1000 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.27A max., λ :0.95; Output: 1000mA,24-40Vdc, 50Vdc max, 40W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-1000 LI EXC-1	Input: 220-240 V~, 50/60 Hz, 0.27A max., λ :0.95; Output: 1000mA,24-40Vdc, 50Vdc max, 40W max.

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager




Certificate of Conformity

Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-1050 LI EXC	Input: 220-240 V~, 50/60 Hz, 0.29A max., λ :0.95; Output: 1050mA,24-38.5Vdc, 52Vdc max., 40.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-1050 LI EXC-1	Input: 220-240 V~, 50/60 Hz, 0.29A max., λ :0.95; Output: 1050mA,24-38.5Vdc, 52Vdc max., 40.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-600 LI-G EXC	Input: 220-240 V~, 50/60 Hz, 0.17A max., λ :0.95; Output: 600mA,24-42Vdc, 50Vdc max., 25.2W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-600 LI-G EXC-1	Input: 220-240 V~, 50/60 Hz, 0.17A max., λ :0.95; Output: 600mA,24-42Vdc, 50Vdc max., 25.2W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-650 LI-G EXC	Input: 220-240 V~, 50/60 Hz, 0.19A max., λ :0.95; Output: 650mA,24-42Vdc, 50Vdc max., 27.3W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-650 LI-G EXC-1	Input: 220-240 V~, 50/60 Hz, 0.19A max., λ :0.95; Output: 650mA,24-42Vdc, 50Vdc max., 27.3W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-700 LI-G EXC	Input: 220-240 V~, 50/60 Hz, 0.2A max., λ :0.95; Output: 700mA,24-42Vdc, 50Vdc max., 29.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-700 LI-G EXC-1	Input: 220-240 V~, 50/60 Hz, 0.2A max., λ :0.95; Output: 700mA,24-42Vdc, 50Vdc max., 29.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-750 LI-G EXC	Input: 220-240 V~, 50/60 Hz, 0.22A max., λ :0.95; Output: 750mA,24-42Vdc, 50Vdc max., 31.5W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-750 LI-G EXC-1	Input: 220-240 V~, 50/60 Hz, 0.22A max., λ :0.95; Output: 750mA,24-42Vdc, 50Vdc max., 31.5W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-800 LI-G EXC	Input: 220-240 V~, 50/60 Hz, 0.23A max., λ :0.95; Output: 800mA,24-42Vdc, 50Vdc max., 33.6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-800 LI-G EXC-1	Input: 220-240 V~, 50/60 Hz, 0.23A max., λ :0.95; Output: 800mA,24-42Vdc, 50Vdc max., 33.6W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-850 LI-G EXC	Input: 220-240 V~, 50/60 Hz, 0.25A max., λ :0.95; Output: 850mA,24-42Vdc, 50Vdc max., 35.7W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-850 LI-G EXC-1	Input: 220-240 V~, 50/60 Hz, 0.25A max., λ :0.95; Output: 850mA,24-42Vdc, 50Vdc max., 35.7W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-900 LI-G EXC	Input: 220-240 V~, 50/60 Hz, 0.26A max., λ :0.95; Output: 900mA,24-42Vdc, 50Vdc max., 37.8W max.

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Certificate of Conformity

Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-900 LI-G EXC-1	Input: 220-240 V~, 50/60 Hz, 0.26A max., λ :0.95; Output: 900mA,24-42Vdc, 50Vdc max, 37.8W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-950 LI-G EXC	Input: 220-240 V~, 50/60 Hz, 0.27A max., λ :0.95; Output: 950mA,24-42Vdc, 50Vdc max, 39.9W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-950 LI-G EXC-1	Input: 220-240 V~, 50/60 Hz, 0.27A max., λ :0.95; Output: 950mA,24-42Vdc, 50Vdc max, 39.9W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-1000 LI-G EXC	Input: 220-240 V~, 50/60 Hz, 0.27A max., λ :0.95; Output: 1000mA,24-40Vdc, 50Vdc max, 40W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-1000 LI-G EXC-1	Input: 220-240 V~, 50/60 Hz, 0.27A max., λ :0.95; Output: 1000mA,24-40Vdc, 50Vdc max, 40W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-1050 LI-G EXC	Input: 220-240 V~, 50/60 Hz, 0.29A max., λ :0.95; Output: 1050mA,24-38.5Vdc, 52Vdc max, 40.4W max.
Power Supply or Charger	LED Power Supply	EAGLERISE	LS-40-1050 LI-G EXC-1	Input: 220-240 V~, 50/60 Hz, 0.29A max., λ :0.95; Output: 1050mA,24-38.5Vdc, 52Vdc max, 40.4W max.

RELEVANT TRADEMARK (S)

COMMENTS OR CONDITIONS ON THE CERTIFICATION

Classified as do not cover

End of document

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Conformity remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager


