


ATTESTATION OF CONFORMITY

Issued to: Foshan Eaglerise Power Science & Technology (Shunde) Co., Ltd.
No.4, East Huanzhen Road, Beijiao, Shunde, 528000 Foshan, Guangdong, China

For the product: LED driver

Trade name:  EAGLERISE

Type/Model: LS-45-24 DALI2 LI, LS-80-24 DALI2 LI, LS-150-24 DALI2 LI,
LS-45-24 DALI-2 LI, LS-80-24 DALI-2 LI, LS-150-24 DALI-2 LI,
LS-150-24 DALI-2 LI2

Ratings: Class II, IP20, SELV, Independent type, constant voltage, safety isolating non-Inherently short-circuit proof, 110 °C thermal protection;
Other information refer to Attachment 5 of test report for details

Manufactured by: Foshan Eaglerise Power Science & Technology (Shunde) Co., Ltd.
No.4, East Huanzhen Road, Beijiao, Shunde, 528000 Foshan, Guangdong, China

Requirements: EN 61347-1:2015 + A1:2021
EN 61347-2-13:2014 + A1:2017
EN 62493:2015

This Attestation is granted on account of an examination by DEKRA, the results of which are laid down in a confidential file no 4397937.50.

This Attestation implies that the examined types are in accordance with the standards designated under the Low Voltage Directive (LVD) 2014/35/EU.

The examination has been carried out on one single specimen or several specimens of the product, submitted by the manufacturer. The Attestation does not include an assessment of the manufacturer's production. Conformity of his production with the specimen tested by DEKRA is not the responsibility of DEKRA.

The CE marking may be affixed on the product if all relevant and effective EC directives are complied with.

Arnhem, 13 January 2023

Number: 4397937.01AOC

DEKRA Testing and Certification (Shanghai) Ltd.,
Guangzhou Branch



Miranda Zhou
Certification Manager

© Integral publication of this attestation and adjoining reports is allowed



Annex

Document no. : 4397765.02AOC

Model list:

Basic code	Type description	CCT	Watt.	Length (mm)	LED quantity (pcs)	Driver PCB	Voltage and frequency	Trade mark
AC46401	LEDTUBE T5HF L8 SHORT V 288 4W/830	3000K	4W	288	21	Same PCB layout, different component parameter.	17-40 V, 25-75 kHz	LEDVANCE
AC46402	LEDTUBE T5HF L8 SHORT V 288 4W/840	4000K	4W	288	21		30-55 V, 25-75 kHz	
AC46403	LEDTUBE T5HF L13 SHORT V 517 7W/830	3000K	7W	517	45			
AC46404	LEDTUBE T5HF L13 SHORT V 517 7W/840	4000K	7W	517	45			
AC47861	LEDTUBE T5HF L8 SHORT 288 4W/830	3000K	4W	288	21	Same PCB layout, different component parameter.	17-40 V, 25-75 kHz	OSRAM

End