



# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

**CERTIFICATE NO.:** 2022011002479573

**Valid from:** Jan.16,2023

**Valid until:** May.15,2027

<b>NAME AND REGISTERED ADDRESS OF THE APPLICANT</b>	Eaglerise Electric & Electronic (China) Co., Ltd. No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong Province, P.R.China
<b>NAME AND REGISTERED ADDRESS OF THE MANUFACTURER</b>	Eaglerise Electric & Electronic (China) Co., Ltd. No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong Province, P.R.China
<b>NAME AND LOCATION OF THE FACTORY</b>	Eaglerise Electric & Electronic (Ji An) Co., Ltd. Southwest Corner, Crossing Between Panlong Road And Chaoyang Road, Industrial Park, Ji An County, Jiangxi Province, P.R.China
<b>PRODUCT MODEL(S)</b>	A.C. Supplied Electronic Controlgear For LED Modules ( Independent, Constant Current Mode, SELV,Non-dimmable, ta:40/45/50/55°C, tc:70/75/80°C, Class II, IP20, Suitable For Direct Mounting On Normally Flammable Material, Temperature Declared Thermally Protected: 110°C ) See Appendix;220-240V ~ 50/60Hz.
<b>STANDARDS AND TECHNICAL REQUIREMENTS</b>	GB/T 17743-2021;GB 19510.1-2009;GB 19510.14-2009

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C10-01:2014)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Date of original issued: Jun.27,2022

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: [www.cnca.gov.cn](http://www.cnca.gov.cn)



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE



# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2022011002479573

page 1 of 9

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

序号	型号	输入			输出				ta (°C)	tc (°C)
		电压 (V~)	最大电 流(A)	频率 (Hz)	恒流 (mA)	工作电压 (Vdc)	最大输出 电压 (Vdc)	最大功率 (W)		
1.	LS-8-120 SI ECO	220-240	0.08	50/60	120	30-42	59	5.1	45	70
2.	LS-8-150 SI ECO	220-240	0.09	50/60	150	30-42	59	6.3	45	70
3.	LS-8-180 SI ECO	220-240	0.11	50/60	180	30-42	59	7.6	45	70
4.	LS-8-200 SI ECO	220-240	0.12	50/60	200	30-42	59	8.4	45	70
5.	LS-8-250 SI ECO	220-240	0.1	50/60	250	16-26	37	6.5	45	70
6.	LS-8-300 SI ECO	220-240	0.1	50/60	300	15-24	40	7.2	45	70
7.	LS-8-350 SI ECO	220-240	0.12	50/60	350	15-24	35	8.4	45	70
8.	LS-8-400 SI ECO	220-240	0.12	50/60	400	12-20	30	8	45	70
9.	LS-8-450 SI ECO	220-240	0.12	50/60	450	11-18	30	8.1	45	70
10.	LS-8-500 SI ECO	220-240	0.12	50/60	500	10-16	26	8	45	70
11.	LS-8-550 SI ECO	220-240	0.12	50/60	550	9-14	25	7.7	45	70
12.	LS-8-600 SI ECO	220-240	0.12	50/60	600	8-13	25	7.8	45	70
13.	LS-12-250 SI ECO	220-240	0.15	50/60	250	30-42	59	10.5	45	70
14.	LS-12-300 SI ECO	220-240	0.18	50/60	300	30-42	59	12.6	45	70
15.	LS-12-350 SI ECO	220-240	0.2	50/60	350	27-40	57	14	45	70
16.	LS-12-400 SI ECO	220-240	0.18	50/60	400	20-30	45	12	45	70
17.	LS-12-450 SI ECO	220-240	0.18	50/60	450	16-26	39	11.7	45	70
18.	LS-12-500 SI ECO	220-240	0.19	50/60	500	14-26	39	13	45	70
19.	LS-12-550 SI ECO	220-240	0.19	50/60	550	12-21	32	11.6	45	70
20.	LS-12-600 SI ECO	220-240	0.19	50/60	600	11-20	31	12	45	70
21.	LS-21-300 SI ECO	220-240	0.3	50/60	300	50-70	90	21	45	80
22.	LS-21-350 SI ECO	220-240	0.3	50/60	350	42-60	80	21	45	80
23.	LS-21-400 SI ECO	220-240	0.3	50/60	400	27-42	55	16.8	45	80
24.	LS-21-450 SI ECO	220-240	0.3	50/60	450	27-42	55	18.9	45	80
25.	LS-21-500 SI ECO	220-240	0.3	50/60	500	27-42	55	21	45	80



CHINA QUALITY CERTIFICATION CENTRE



# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2022011002479573

page 2 of 9

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

序号	型号	输入			输出				ta (°C)	tc (°C)
		电压 (V~)	最大电 流(A)	频率 (Hz)	恒流 (mA)	工作电压 (Vdc)	最大输出 电压 (Vdc)	最大功率 (W)		
26.	LS-21-550 SI ECO	220-240	0.3	50/60	550	27-40	55	22	45	80
27.	LS-21-600 SI ECO	220-240	0.3	50/60	600	27-39	55	23.4	45	80
28.	LS-21-650 SI ECO	220-240	0.3	50/60	650	20-32	50	20.8	45	80
29.	LS-21-700 SI ECO	220-240	0.3	50/60	700	18-30	50	21	45	80
30.	LS-8-220 SI ECO	220-240	0.07	50/60	220	30-38.5	50	8.5	45	70
31.	LS-3-150 SI ECO	220-240	0.07	50/60	150	5-12	24	1.8	50	75
32.	LS-3-200 SI ECO	220-240	0.07	50/60	200	5-12	24	2.4	50	75
33.	LS-3-250 SI ECO	220-240	0.07	50/60	250	5-12	24	3	50	75
34.	LS-3-300 SI ECO	220-240	0.07	50/60	300	5-12	24	3.6	50	75
35.	LS-3-350 SI ECO	220-240	0.07	50/60	350	5-12	24	4.2	50	75
36.	LS-3-400 SI ECO	220-240	0.07	50/60	400	2.5-4.5	16	1.8	50	75
37.	LS-3-450 SI ECO	220-240	0.07	50/60	450	2.5-4.5	16	2.03	50	75
38.	LS-3-500 SI ECO	220-240	0.07	50/60	500	2.5-4.5	16	2.25	50	75
39.	LS-3-550 SI ECO	220-240	0.07	50/60	550	2.5-4.5	16	2.48	50	75
40.	LS-3-600 SI ECO	220-240	0.07	50/60	600	2.5-4.5	16	2.7	50	75
41.	LS-3-650 SI ECO	220-240	0.07	50/60	650	2.5-4.5	10	2.9	50	75
42.	LS-3-700 SI ECO	220-240	0.07	50/60	700	2.5-4.5	10	3.15	50	75
43.	LS-6-120 SI ECO	220-240	0.11	50/60	120	27-40	59	4.8	50	80
44.	LS-6-150 SI ECO	220-240	0.11	50/60	150	27-40	59	6	50	80
45.	LS-6-180 SI ECO	220-240	0.11	50/60	180	27-40	59	7.2	50	80
46.	LS-6-200 SI ECO	220-240	0.11	50/60	200	27-40	59	8	50	80
47.	LS-6-250 SI ECO	220-240	0.11	50/60	250	10-24	45	6	50	80
48.	LS-6-300 SI ECO	220-240	0.11	50/60	300	8-20	40	6	50	80
49.	LS-6-350 SI ECO	220-240	0.11	50/60	350	8-18	40	6.3	50	80
50.	LS-6-400 SI ECO	220-240	0.11	50/60	400	5-15	30	6	50	80



CHINA QUALITY CERTIFICATION CENTRE



# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2022011002479573

page 3 of 9

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

序号	型号	输入			输出				ta (°C)	tc (°C)
		电压 (V~)	最大电 流(A)	频率 (Hz)	恒流 (mA)	工作电压 (Vdc)	最大输出 电压 (Vdc)	最大功率 (W)		
51.	LS-6-450 SI ECO	220-240	0.11	50/60	450	5-13.5	30	6.1	50	80
52.	LS-6-500 SI ECO	220-240	0.11	50/60	500	5-12	30	6	50	80
53.	LS-6-550 SI ECO	220-240	0.11	50/60	550	5-11	30	6.05	50	80
54.	LS-6-600 SI ECO	220-240	0.11	50/60	600	4-9	25	5.4	50	80
55.	LS-6-650 SI ECO	220-240	0.11	50/60	650	4-9	25	5.85	50	80
56.	LS-6-700 SI ECO	220-240	0.11	50/60	700	4-9	25	6.3	50	80
57.	LS-3-150 SI E	220-240	0.07	50/60	150	5-12	24	1.8	50	75
58.	LS-3-200 SI E	220-240	0.07	50/60	200	5-12	24	2.4	50	75
59.	LS-3-250 SI E	220-240	0.07	50/60	250	5-12	24	3	50	75
60.	LS-3-300 SI E	220-240	0.07	50/60	300	5-12	24	3.6	50	75
61.	LS-3-350 SI E	220-240	0.07	50/60	350	5-12	24	4.2	50	75
62.	LS-3-400 SI E	220-240	0.07	50/60	400	2.5-4.5	16	1.8	50	75
63.	LS-3-450 SI E	220-240	0.07	50/60	450	2.5-4.5	16	2.03	50	75
64.	LS-3-500 SI E	220-240	0.07	50/60	500	2.5-4.5	16	2.25	50	75
65.	LS-3-550 SI E	220-240	0.07	50/60	550	2.5-4.5	16	2.48	50	75
66.	LS-3-600 SI E	220-240	0.07	50/60	600	2.5-4.5	16	2.7	50	75
67.	LS-3-650 SI E	220-240	0.07	50/60	650	2.5-4.5	10	2.9	50	75
68.	LS-3-700 SI E	220-240	0.07	50/60	700	2.5-4.5	10	3.15	50	75
69.	LS-6-120 SI E	220-240	0.11	50/60	120	27-40	59	4.8	50	80
70.	LS-6-150 SI E	220-240	0.11	50/60	150	27-40	59	6	50	80
71.	LS-6-180 SI E	220-240	0.11	50/60	180	27-40	59	7.2	50	80
72.	LS-6-200 SI E	220-240	0.11	50/60	200	27-40	59	8	50	80
73.	LS-6-250 SI E	220-240	0.11	50/60	250	10-24	45	6	50	80
74.	LS-6-300 SI E	220-240	0.11	50/60	300	8-20	40	6	50	80
75.	LS-6-350 SI E	220-240	0.11	50/60	350	8-18	40	6.3	50	80



CHINA QUALITY CERTIFICATION CENTRE



# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2022011002479573

page 4 of 9

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

序号	型号	输入			输出				ta (°C)	tc (°C)
		电压 (V~)	最大电 流(A)	频率 (Hz)	恒流 (mA)	工作电压 (Vdc)	最大输出 电压 (Vdc)	最大功率 (W)		
76.	LS-6-400 SI E	220-240	0.11	50/60	400	5-15	30	6	50	80
77.	LS-6-450 SI E	220-240	0.11	50/60	450	5-13.5	30	6.1	50	80
78.	LS-6-500 SI E	220-240	0.11	50/60	500	5-12	30	6	50	80
79.	LS-6-550 SI E	220-240	0.11	50/60	550	5-11	30	6.05	50	80
80.	LS-6-600 SI E	220-240	0.11	50/60	600	4-9	25	5.4	50	80
81.	LS-6-650 SI E	220-240	0.11	50/60	650	4-9	25	5.85	50	80
82.	LS-6-700 SI E	220-240	0.11	50/60	700	4-9	25	6.3	50	80
83.	LS-8-120 LI EXC	220-240	0.07	50/60	120	27-50	59	6	55	75
84.	LS-8-150 LI EXC	220-240	0.07	50/60	150	27-50	59	7.5	55	75
85.	LS-8-180 LI EXC	220-240	0.07	50/60	180	22-42	55	7.6	55	75
86.	LS-8-200 LI EXC	220-240	0.07	50/60	200	22-42	55	8.4	55	75
87.	LS-8-220 LI EXC	220-240	0.07	50/60	220	22-42	55	9.24	55	75
88.	LS-8-250 LI EXC	220-240	0.07	50/60	250	14-27	45	6.75	55	75
89.	LS-8-300 LI EXC	220-240	0.07	50/60	300	14-27	45	8.1	55	75
90.	LS-8-350 LI EXC	220-240	0.07	50/60	350	12-24	35	8.4	55	75
91.	LS-12-250 LI EXC	220-240	0.09	50/60	250	24-42	55	10.5	45	75
92.	LS-12-300 LI EXC	220-240	0.09	50/60	300	24-42	55	12.6	45	75
93.	LS-12-350 LI EXC	220-240	0.09	50/60	350	24-40	55	14	45	75
94.	LS-20-350 LI EXC	220-240	0.16	50/60	350	40-60	75	21	45	80
95.	LS-20-400 LI EXC	220-240	0.16	50/60	400	24-42	55	16.8	45	80
96.	LS-20-450 LI EXC	220-240	0.16	50/60	450	24-42	55	18.9	45	80
97.	LS-20-500 LI EXC	220-240	0.16	50/60	500	24-42	55	21	45	80
98.	LS-20-550 LI EXC	220-240	0.16	50/60	550	24-40	55	22	45	80
99.	LS-20-600 LI EXC	220-240	0.16	50/60	600	24-40	55	24	45	80
100.	LS-20-700 LI EXC	220-240	0.16	50/60	700	18-30	45	21	45	80



CHINA QUALITY CERTIFICATION CENTRE



# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2022011002479573

page 5 of 9

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

序号	型号	输入			输出				ta (°C)	tc (°C)
		电压 (V~)	最大电 流(A)	频率 (Hz)	恒流 (mA)	工作电压 (Vdc)	最大输出 电压 (Vdc)	最大功率 (W)		
101.	LS-21-250 SI1 ECO	220-240	0.3	50/60	250	50-80	95	20	45	80
102.	LS-21-300 SI1 ECO	220-240	0.3	50/60	300	40-70	90	21	45	80
103.	LS-21-350 SI1 ECO	220-240	0.3	50/60	350	42-60	80	21	45	80
104.	LS-21-400 SI1 ECO	220-240	0.3	50/60	400	27-42	55	16.8	45	80
105.	LS-21-450 SI1 ECO	220-240	0.3	50/60	450	27-42	55	18.9	45	80
106.	LS-21-500 SI1 ECO	220-240	0.3	50/60	500	27-42	55	21	45	80
107.	LS-21-550 SI1 ECO	220-240	0.3	50/60	550	27-40	55	22	45	80
108.	LS-21-600 SI1 ECO	220-240	0.3	50/60	600	27-39	55	23.4	45	80
109.	LS-21-650 SI1 ECO	220-240	0.3	50/60	650	20-32	50	20.8	45	80
110.	LS-21-700 SI1 ECO	220-240	0.3	50/60	700	18-30	50	21	45	80
111.	LS-8-120 SI1 ECO	220-240	0.08	50/60	120	30-42	59	5.1	45	70
112.	LS-8-150 SI1 ECO	220-240	0.09	50/60	150	30-42	59	6.3	45	70
113.	LS-8-180 SI1 ECO	220-240	0.11	50/60	180	30-42	59	7.6	45	70
114.	LS-8-200 SI1 ECO	220-240	0.12	50/60	200	30-42	59	8.4	45	70
115.	LS-8-220 SI1 ECO	220-240	0.07	50/60	220	30-38.5	59	8.5	45	70
116.	LS-8-250 SI1 ECO	220-240	0.1	50/60	250	16-26	42	6.5	45	70
117.	LS-8-300 SI1 ECO	220-240	0.1	50/60	300	15-24	40	7.2	45	70
118.	LS-8-350 SI1 ECO	220-240	0.12	50/60	350	15-24	40	8.4	45	70
119.	LS-8-400 SI1 ECO	220-240	0.12	50/60	400	12-20	35	8	45	70
120.	LS-8-450 SI1 ECO	220-240	0.12	50/60	450	11-18	32	8.1	45	70
121.	LS-8-500 SI1 ECO	220-240	0.12	50/60	500	10-16	26	8	45	70
122.	LS-8-550 SI1 ECO	220-240	0.12	50/60	550	9-14	25	7.7	45	70
123.	LS-8-600 SI1 ECO	220-240	0.12	50/60	600	8-13	25	7.8	45	70
124.	LS-12-250 SI1 ECO	220-240	0.15	50/60	250	30-42	59	10.5	45	70
125.	LS-12-300 SI1 ECO	220-240	0.18	50/60	300	30-42	59	12.6	45	70



CHINA QUALITY CERTIFICATION CENTRE



# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2022011002479573

page 6 of 9

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

序号	型号	输入			输出				ta (°C)	tc (°C)
		电压 (V~)	最大电 流(A)	频率 (Hz)	恒流 (mA)	工作电压 (Vdc)	最大输出 电压 (Vdc)	最大功率 (W)		
126.	LS-12-350 SI1 ECO	220-240	0.2	50/60	350	27-40	57	14	45	70
127.	LS-12-400 SI1 ECO	220-240	0.18	50/60	400	20-30	45	12	45	70
128.	LS-12-450 SI1 ECO	220-240	0.18	50/60	450	16-26	42	11.7	45	70
129.	LS-12-500 SI1 ECO	220-240	0.19	50/60	500	14-26	42	13	45	70
130.	LS-12-550 SI1 ECO	220-240	0.19	50/60	550	12-21	35	11.6	45	70
131.	LS-12-600 SI1 ECO	220-240	0.19	50/60	600	11-20	35	12	45	70
132.	LS-21-250 SI1 E	220-240	0.3	50/60	250	50-80	95	20	45	80
133.	LS-21-300 SI1 E	220-240	0.3	50/60	300	40-70	90	21	45	80
134.	LS-21-350 SI1 E	220-240	0.3	50/60	350	42-60	80	21	45	80
135.	LS-21-400 SI1 E	220-240	0.3	50/60	400	27-42	55	16.8	45	80
136.	LS-21-450 SI1 E	220-240	0.3	50/60	450	27-42	55	18.9	45	80
137.	LS-21-500 SI1 E	220-240	0.3	50/60	500	27-42	55	21	45	80
138.	LS-21-550 SI1 E	220-240	0.3	50/60	550	27-40	55	22	45	80
139.	LS-21-600 SI1 E	220-240	0.3	50/60	600	27-39	55	23.4	45	80
140.	LS-21-650 SI1 E	220-240	0.3	50/60	650	20-32	50	20.8	45	80
141.	LS-21-700 SI1 E	220-240	0.3	50/60	700	18-30	50	21	45	80
142.	LS-8-120 SI1 E	220-240	0.08	50/60	120	30-42	59	5.1	45	70
143.	LS-8-150 SI1 E	220-240	0.09	50/60	150	30-42	59	6.3	45	70
144.	LS-8-180 SI1 E	220-240	0.11	50/60	180	30-42	59	7.6	45	70
145.	LS-8-200 SI1 E	220-240	0.12	50/60	200	30-42	59	8.4	45	70
146.	LS-8-220 SI1 E	220-240	0.07	50/60	220	30-38.5	59	8.5	45	70
147.	LS-8-250 SI1 E	220-240	0.1	50/60	250	16-26	42	6.5	45	70
148.	LS-8-300 SI1 E	220-240	0.1	50/60	300	15-24	40	7.2	45	70
149.	LS-8-350 SI1 E	220-240	0.12	50/60	350	15-24	40	8.4	45	70
150.	LS-8-400 SI1 E	220-240	0.12	50/60	400	12-20	35	8	45	70



CHINA QUALITY CERTIFICATION CENTRE





# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2022011002479573

page 7 of 9

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

序号	型号	输入			输出				ta (°C)	tc (°C)
		电压 (V~)	最大电 流(A)	频率 (Hz)	恒流 (mA)	工作电压 (Vdc)	最大输出 电压 (Vdc)	最大功率 (W)		
151.	LS-8-450 SI1 E	220-240	0.12	50/60	450	11-18	32	8.1	45	70
152.	LS-8-500 SI1 E	220-240	0.12	50/60	500	10-16	26	8	45	70
153.	LS-8-550 SI1 E	220-240	0.12	50/60	550	9-14	25	7.7	45	70
154.	LS-8-600 SI1 E	220-240	0.12	50/60	600	8-13	25	7.8	45	70
155.	LS-12-250 SI1 E	220-240	0.15	50/60	250	30-42	59	10.5	45	70
156.	LS-12-300 SI1 E	220-240	0.18	50/60	300	30-42	59	12.6	45	70
157.	LS-12-350 SI1 E	220-240	0.2	50/60	350	27-40	57	14	45	70
158.	LS-12-400 SI1 E	220-240	0.18	50/60	400	20-30	45	12	45	70
159.	LS-12-450 SI1 E	220-240	0.18	50/60	450	16-26	42	11.7	45	70
160.	LS-12-500 SI1 E	220-240	0.19	50/60	500	14-26	42	13	45	70
161.	LS-12-550 SI1 E	220-240	0.19	50/60	550	12-21	35	11.6	45	70
162.	LS-12-600 SI1 E	220-240	0.19	50/60	600	11-20	35	12	45	70
163.	LS-8-120 SI E	220-240	0.08	50/60	120	30-42	59	5.1	45	70
164.	LS-8-150 SI E	220-240	0.09	50/60	150	30-42	59	6.3	45	70
165.	LS-8-180 SI E	220-240	0.11	50/60	180	30-42	59	7.6	45	70
166.	LS-8-200 SI E	220-240	0.12	50/60	200	30-42	59	8.4	45	70
167.	LS-8-220 SI E	220-240	0.07	50/60	220	30-38.5	50	8.5	45	70
168.	LS-8-250 SI E	220-240	0.1	50/60	250	16-26	37	6.5	45	70
169.	LS-8-300 SI E	220-240	0.1	50/60	300	15-24	40	7.2	45	70
170.	LS-8-350 SI E	220-240	0.12	50/60	350	15-24	35	8.4	45	70
171.	LS-8-400 SI E	220-240	0.12	50/60	400	12-20	30	8	45	70
172.	LS-8-450 SI E	220-240	0.12	50/60	450	11-18	30	8.1	45	70
173.	LS-8-500 SI E	220-240	0.12	50/60	500	10-16	26	8	45	70
174.	LS-8-550 SI E	220-240	0.12	50/60	550	9-14	25	7.7	45	70
175.	LS-8-600 SI E	220-240	0.12	50/60	600	8-13	25	7.8	45	70



CHINA QUALITY CERTIFICATION CENTRE





# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2022011002479573

page 8 of 9

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

序号	型号	输入			输出				ta (°C)	tc (°C)
		电压 (V~)	最大电 流(A)	频率 (Hz)	恒流 (mA)	工作电压 (Vdc)	最大输出 电压 (Vdc)	最大功率 (W)		
176.	LS-12-250 SI E	220-240	0.15	50/60	250	30-42	59	10.5	45	70
177.	LS-12-300 SI E	220-240	0.18	50/60	300	30-42	59	12.6	45	70
178.	LS-12-350 SI E	220-240	0.2	50/60	350	27-40	57	14	45	70
179.	LS-12-400 SI E	220-240	0.18	50/60	400	20-30	45	12	45	70
180.	LS-12-450 SI E	220-240	0.18	50/60	450	16-26	39	11.7	45	70
181.	LS-12-500 SI E	220-240	0.19	50/60	500	14-26	39	13	45	70
182.	LS-12-550 SI E	220-240	0.19	50/60	550	12-21	32	11.6	45	70
183.	LS-12-600 SI E	220-240	0.19	50/60	600	11-20	31	12	45	70
184.	LS-21-300 SI E	220-240	0.3	50/60	300	50-70	90	21	45	80
185.	LS-21-350 SI E	220-240	0.3	50/60	350	42-60	80	21	45	80
186.	LS-21-400 SI E	220-240	0.3	50/60	400	27-42	55	16.8	45	80
187.	LS-21-450 SI E	220-240	0.3	50/60	450	27-42	55	18.9	45	80
188.	LS-21-500 SI E	220-240	0.3	50/60	500	27-42	55	21	45	80
189.	LS-21-550 SI E	220-240	0.3	50/60	550	27-40	55	22	45	80
190.	LS-21-600 SI E	220-240	0.3	50/60	600	27-39	55	23.4	45	80
191.	LS-21-650 SI E	220-240	0.3	50/60	650	20-32	50	20.8	45	80
192.	LS-21-700 SI E	220-240	0.3	50/60	700	18-30	50	21	45	80
193.	LS-8-180 SI E1	220-240	0.11	50/60	180	30-42	59	7.56	45	80
194.	LS-8-200 SI E1	220-240	0.11	50/60	200	30-42	59	8.4	45	80
195.	LS-8-220 SI E1	220-240	0.11	50/60	220	30-42	59	9.24	45	80
196.	LS-8-700 SI E1	220-240	0.11	50/60	700	8-13	24	9.1	40	80
197.	LS-6-220 SI ECO	220-240	0.11	50/60	220	27-40	59	8.8	50	80
198.	LS-6-220 SI E	220-240	0.11	50/60	220	27-40	59	8.8	50	80
199.	LS-3-100 SI ECO	220-240	0.11	50/60	100	27-40	59	4	50	75
200.	LS-3-100 SI E	220-240	0.11	50/60	100	27-40	59	4	50	75



CHINA QUALITY CERTIFICATION CENTRE



# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2022011002479573

page 9 of 9

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

序号	型号	输入			输出				ta (°C)	tc (°C)
		电压 (V~)	最大电 流(A)	频率 (Hz)	恒流 (mA)	工作电压 (Vdc)	最大输出 电压 (Vdc)	最大功率 (W)		
1、 Input : 220-240V~ 50/60Hz ;										



CHINA QUALITY CERTIFICATION CENTRE