

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Name and address of the applicant

Name and address of the manufacturer

Name and address of the factory

Note: When more than one factory, please report on page 2

Ratings and Principal characteristics

Customer's Testing Facility (CTF) Stage used

Model/Type Ref

Trademark /Brand (If any)

Additional information(If necessary may also be reported on Page 2)

A sample of the product was tested and found to be in conformity with

As shown in the Test Report Ref. No. which forms part of this Certificate

LED Power Supply

Foshan Eaglerise Power Science & Technology (Shunde) Co., Ltd. No.4, East Huanzhen Road, Beijiao Shunde, Foshan, Guangdong China

Foshan Eaglerise Power Science & Technology (Shunde) Co., Ltd. No.4, East Huanzhen Road, Beijiao Shunde, Foshan, Guangdong

China

See next page(s)

Additional Information on Page 2

PRI: LV supply: max. 0.4 A, 220-240 V~, 50/60 Hz,

PF:0.65C-0.95 (For FMS-35-750 LD1 and FMS-35-750 LD-TP), PF:0.85C-0.95 (For FMS-55-1050 LD1 and FMS-55-1050 LD-TP), PF:0.8C-0.95 (For MS-12-yyyy LI-TP), PF:0.9C-0.95 (For MS-20-yyyy LI-TP and MS-40-yyyy LI-TP), PF:0.95 (For MS-60-yyyy LI-TP)

FMS-35-750 LD1, FMS-35-750 LD-TP, FMS-55-1050 LD1, FMS-55-1050 LD-TP, MS-xx-yyyy

SEC: max. 60.9 W, max. 1.5 A, 15-52 Vd.c. (under load), max. 63 Vd.c. (no-load).

EAGLERISE

Additional Information on Page 2

IEC 61347-1:2015, IEC 61347-1:2015/AMD1:2017 IEC 61347-2-13:2014, IEC 61347-2-13:2014/AMD1:2016

REP004057

This CB Test Certificate is issued by the National Certification Body

Nemko

Philip Pedersen vei 11, NO-1366 Lysaker, Norway

Date: 29-12-2022

Signature: Sweet Yuan

Certification department



NO125248

Foshan Eaglerise Power Science & Technology (Shunde) Co., Ltd. No.4, East Huanzhen Road, Beijiao Shunde, Foshan, Guangdong China

EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD West Zone, Ji An County Industrial Park, Ji an County Jiangxi Province China

Additional Information (if necessary)

Built-in type, SELV, constant current output, thermal protected 110 °C, ta: 50 °C/60 °C, tc: 75 °C / 80 °C/85 °C. The 'xx' in the type designation can be 12, 20, 40 or 60, indicating the approximate rated output wattage in Watt. The 'yyyy' is for the output current and represents the number from 200 to 1500, for example, 200 means the output current is 200 mA, 1500 means the output current is 1500 mA.



Philip Pedersen vei 11, NO-1366 Lysaker, Norway Date: 29-12-2022

Signature: Sweet Yuan

Certification department