

CB TEST CERTIFICATE CERTIFICAT D'ESSAI OCProduct
ProduitName and address of the applicant
Nom et adresse du demandeurName and address of the manufacturer
Nom et adresse du fabricantName and address of the factory
Nom et adresse de l'usineNote: When more than one factory, please report on page 2
Note: Lorsque il y plus d'une usine, veuillez utiliser la deuxième pageRatings and principal characteristics
Valeurs nominales et caractéristiques principalesTrademark (if any)
Marque de fabrique (si elle existe)Type of Manufacturer's Testing Laboratories used
Type de programme du laboratoire d'essais constructeurModel / Type Ref.
Ref. De typeAdditional information (if necessary may also be reported on page 2)
Les informations complémentaires (si nécessaire, peuvent être indiqués sur la deuxième pageA sample of the product was tested and found to be in conformity with
Un échantillon de ce produit a été essayé et a été considéré conforme à laAs shown in the Test Report Ref. No. which forms part of this Certificate
Comme indiqué dans le Rapport de tests numéro de référence qui constitue partie de ce CertificatThis CB Test Certificate is issued by the National Certification Body
Ce Certificat de test OC est établi par l'Organisme National de Certification

Dimmable LED Power Supply

Eaglerise Electric & Electronic (China) Co., Ltd.
No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong Province
ChinaEaglerise Electric & Electronic (China) Co., Ltd.
No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong Province
China Additional information on page 2PRI: max. 0.47 A, 220-240 V~, 50/60 Hz,
pf = 0.9C (for LS-12-XXXX ON/OFF LI1);
pf > 0.95 (for LS-21-XXXX ON/OFF LI1, LS-30-XXXX ON/OFF LI1, LS-40-XXXX ON/OFF LI1 and LS-60-XXXX ON/OFF LI1)
SEC: max. 60.4 W, max. 1.05 A, 12-100 Vdc (under load), max.120 Vdc (no-load)
Cl.II

LS-12-XXXX ON/OFF LI1, LS-21-XXXX ON/OFF LI1, LS-30-XXXX ON/OFF LI1, LS-40-XXXX ON/OFF LI1, LS-60-XXXX ON/OFF LI1

 Additional information on page 2IEC 61347-1:2015, IEC 61347-1:2015/AMD1:2017
IEC 61347-2-13:2014, IEC 61347-2-13:2014/AMD1:2016

400325

Eaglerise Electric & Electronic (China) Co.,Ltd. Beijiao Branch
No.4, East Huanzhen Road, Beijiao Shunde
Foshan, Guangdong, 528000
China

EAGLERISE ELECTRIC & ELECTRONIC(JI AN)CO., LTD
West Zone, Ji an County Industrial Park, Ji an County,
Jiangxi Province
China

Additional information(if necessary)

Information complémentaire (si nécessaire)

independent type, SELV, constant current output, thermal protected 110 °C. ta: 45 °C, tc: 80 °C (for LS-12-XXXX ON/OFF LI1 and LS-21-XXXX ON/OFF LI1); ta: 45°C, tc: 85 °C (for LS-30-XXXX ON/OFF LI1, LS-40-XXXX ON/OFF LI1 and LS-60-XXXX ON/OFF LI1) The XXXX is for the output current and represents the number from 300 to 1050, increasing in multiples of 50, for example, 300 means the output current is 300 mA.



Philip Pedersen vei 11,
NO-1366 Lysaker, Norway

Date: 25-06-2020

Jiyea Gim

Signature: Jiyea Gim
Certification Department