



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2021011002393869

Valid from: Aug.12,2022

Valid until: Jun.09,2025

NAME AND REGISTERED ADDRESS OF THE APPLICANT	Eaglerise Electric & Electronic (China) Co., Ltd. No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong Province, P.R.China
NAME AND REGISTERED ADDRESS OF THE MANUFACTURER	Eaglerise Electric & Electronic (China) Co., Ltd. No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong Province, P.R.China
NAME AND LOCATION OF THE FACTORY	Eaglerise Electric & Electronic (Ji An) Co., Ltd. Southwest Corner, Crossing Between Panlong Road And Chaoyang Road, Industrial Park, Ji An County, Jiangxi Province, P.R.China
PRODUCT MODEL(S)	A.C. Supplied Electronic Controlgear For LED Modules (Independent, Constant Voltage Mode, SELV, ta:45°C, ClassII, IP20, Suitable For Direct Mounting On Normally Flammable Material, Temperature Declared Thermally Protected: 110°C) See Appendix. 220-240V ~ 50/60Hz
STANDARDS AND TECHNICAL REQUIREMENTS	GB 17625.1-2012;GB/T 17743-2021;GB 19510.1-2009;GB 19510.14-2009

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C10-01:2014)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Date of original issued: Jun.24,2021

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2021011002393869

page 1 of 1

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

序号	型号	输入			输出		power (W)	ta(°C)	tc (°C)
		电压 (VAC)	最大电流 (A)	频率 (Hz)	恒压 (Vdc)	最大电流 (A)			
1	US-30-12 LI1	220-240	0.24	50/60	12	2.5	30	45	90
2	US-30-24 LI1	220-240	0.24	50/60	24	1.25	30	45	85
3	US-60-12 LI1	220-240	0.46	50/60	12	5	60	45	90
4	US-60-24 LI1	220-240	0.46	50/60	24	2.5	60	45	90
5	US-100-12 LI1	220-240	0.78	50/60	12	8.33	100	45	90
6	US-100-24 LI1	220-240	0.78	50/60	24	4.17	100	45	90
7	US-160-24 LI1	220-240	1	50/60	24	6.67	160	45	90

注：所有型号均为单路输出，其中 US-100-12 LI1, US-100-24 LI1, US-160-24 LI1 为单路输出，但分为 2 个输出端子（两个端子的同极并联），参数列表中的电流和功率为两个输出端子之和，两个输出端子的电压即为参数列表中的电压。



CHINA QUALITY CERTIFICATION CENTRE