



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2023011002558766

Valid from: Jul.20,2023

Valid until: May.04,2028

NAME AND REGISTERED ADDRESS OF THE APPLICANT	Eaglerise Electric & Electronic (China) Co., Ltd. No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong Province, P.R.China
NAME AND REGISTERED ADDRESS OF THE MANUFACTURER	Eaglerise Electric & Electronic (China) Co., Ltd. No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong Province, P.R.China
NAME AND LOCATION OF THE FACTORY	Eaglerise Electric & Electronic (Ji An) Co., Ltd. Southwest Corner, Crossing Between Panlong Road And Chaoyang Road, Industrial Park, Ji An County, Jiangxi Province, P.R.China
PRODUCT MODEL(S)	A.C. Supplied Electronic Controlgear For LED Modules (Built-in, Constant Current Mode, SELV, ta :60°C , tc : 80°C , Temperature Declared Thermally Protected: 110°C) See Appendix. 220-240V ~ 50/60Hz
STANDARDS AND TECHNICAL REQUIREMENTS	GB 17625.1-2022;GB/T 17743-2021;GB 19510.1-2009;GB 19510.14-2009

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C10-01:2014)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2023011002558766

page 1 of 1

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

序号	型号	技术参数
1	MS-40-600 LI	输出: 600mA (恒流), 24-42V $\overline{\text{---}}$, Max. 55V $\overline{\text{---}}$, Max. 25.2W; tc: 80°C
2	MS-40-650 LI	输出: 650mA (恒流), 24-42V $\overline{\text{---}}$, Max. 55V $\overline{\text{---}}$, Max. 27.3W; tc: 80°C
3	MS-40-700 LI	输出: 700mA (恒流), 24-42V $\overline{\text{---}}$, Max. 55V $\overline{\text{---}}$, Max. 29.4W; tc: 80°C
4	MS-40-750 LI	输出: 750mA (恒流), 24-42V $\overline{\text{---}}$, Max. 55V $\overline{\text{---}}$, Max. 31.5W; tc: 80°C
5	MS-40-800 LI	输出: 800mA (恒流), 24-42V $\overline{\text{---}}$, Max. 55V $\overline{\text{---}}$, Max. 33.6W; tc: 80°C
6	MS-40-850 LI	输出: 850mA (恒流), 24-42V $\overline{\text{---}}$, Max. 55V $\overline{\text{---}}$, Max. 35.7W; tc: 80°C
7	MS-40-900 LI	输出: 900mA (恒流), 24-42V $\overline{\text{---}}$, Max. 55V $\overline{\text{---}}$, Max. 37.8W; tc: 80°C
8	MS-40-950 LI	输出: 950mA (恒流), 24-42V $\overline{\text{---}}$, Max. 55V $\overline{\text{---}}$, Max. 39.9W; tc: 80°C
9	MS-40-1000 LI	输出: 1000mA (恒流), 24-40V $\overline{\text{---}}$, Max. 55V $\overline{\text{---}}$, Max. 40W; tc: 80°C
10	MS-40-600 LI-TP	输出: 600mA (恒流), 24-42V $\overline{\text{---}}$, Max. 55V $\overline{\text{---}}$, Max. 25.2W; tc: 80°C
11	MS-40-650 LI-TP	输出: 650mA (恒流), 24-42V $\overline{\text{---}}$, Max. 55V $\overline{\text{---}}$, Max. 27.3W; tc: 80°C
12	MS-40-700 LI-TP	输出: 700mA (恒流), 24-42V $\overline{\text{---}}$, Max. 55V $\overline{\text{---}}$, Max. 29.4W; tc: 80°C
13	MS-40-750 LI-TP	输出: 750mA (恒流), 24-42V $\overline{\text{---}}$, Max. 55V $\overline{\text{---}}$, Max. 31.5W; tc: 80°C
14	MS-40-800 LI-TP	输出: 800mA (恒流), 24-42V $\overline{\text{---}}$, Max. 55V $\overline{\text{---}}$, Max. 33.6W; tc: 80°C
15	MS-40-850 LI-TP	输出: 850mA (恒流), 24-42V $\overline{\text{---}}$, Max. 55V $\overline{\text{---}}$, Max. 35.7W; tc: 80°C
16	MS-40-900 LI-TP	输出: 900mA (恒流), 24-42V $\overline{\text{---}}$, Max. 55V $\overline{\text{---}}$, Max. 37.8W; tc: 80°C
17	MS-40-950 LI-TP	输出: 950mA (恒流), 24-42V $\overline{\text{---}}$, Max. 55V $\overline{\text{---}}$, Max. 39.9W; tc: 80°C
18	MS-40-1000 LI-TP	输出: 1000mA (恒流), 24-40V $\overline{\text{---}}$, Max. 55V $\overline{\text{---}}$, Max. 40W; tc: 80°C

输入: 220-240V~, 50/60Hz



CHINA QUALITY CERTIFICATION CENTRE