

CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

 CERTIFICATE NO.: 2023011002565268
 Valid from: Aug.21,2023

 Valid until: May.03,2028

NAME AND REGISTERED
ADDRESS OF THE APPLICANT

Eaglerise Electric & Electronic (China) Co., Ltd.

No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong

Province, P.R.China

NAME AND REGISTERED

ADDRESS OF THE MANUFACTURER

Eaglerise Electric & Electronic (China) Co., Ltd.

No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong

Province, P.R.China

NAME AND LOCATION

Eaglerise Electric & Electronic (Ji An) Co., Ltd.

OF THE FACTORY

Southwest Corner, Crossing Between Panlong Road And Chaoyang Road, Industrial Park, Ji An County,

Jiangxi Province, P.R.China

PRODUCT MODEL(S)

A.C. Supplied Electronic Controlgear For LED Modules (Built-in, Constant Current Mode, SELV,

Non-dimmable, ta:45°C, tc:80°C/85°C, Temperature Declared Thermally Protected: 110°C)

See Appendix; 220-240V~ 50/60Hz.

STANDARDS AND

GB 17625.1-2022;GB/T 17743-2021;GB 19510.1-2009;GB 19510.14-2009

TECHNICAL REQUIREMENTS

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C10-01:2014)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



http://www.cqc.com.cn

SIGNATURE: 谢肇顺



Tel: +86 10 83886666



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2023011002565268

page1 of 1

Tel: +86 10 83886666

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

<u></u> 型号	输出电流(mA)	输出电压(Vdc)	空载输出电压 (Max.Vdc)	输出功率 Max.(W)	ta(°C)	tc(°C)
SS-8-200 SX E	200	30-42	59	8.4	45	80
SS-12-300 SX E	300	30-42	50	12.6	45	85

输入: 220-240V~ 50/60Hz

