

CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2023011002566704

Valid from: Aug.25,2023 Valid until:May.03,2028

NAME AND REGISTERED
ADDRESS OF THE APPLICANT

Eaglerise Electric & Electronic (China) Co., Ltd.

No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong

Province, P.R.China

NAME AND REGISTERED

ADDRESS OF THE MANUFACTURER

Eaglerise Electric & Electronic (China) Co., Ltd.

No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong

Province, P.R.China

NAME AND LOCATION

Eaglerise Electric & Electronic (Ji An) Co., Ltd.

OF THE FACTORY

Southwest Corner, Crossing Between Panlong Road And Chaoyang Road, Industrial Park, Ji An County,

Jiangxi Province, P.R.China

PRODUCT MODEL(S)

A.C. Supplied Electronic Controlgear For LED Modules (Independent, Constant Current Mode, SELV,

IP20, Class II, Non-dimmable, ta:50°C, tc:75°C, Suitable For Direct Mounting On Normally Flammable

Material, Temperature Declared Thermally Protected: 110°C)

See Appendix; 220-240V~ 50/60Hz.

STANDARDS AND

GB 17625.1-2022;GB/T 17743-2021;GB 19510.1-2009;GB 19510.14-2009

TECHNICAL REQUIREMENTS

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C10-01:2014)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



SIGNATURE: 谢肇煦



Tel: +86 10 83886666



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2023011002566704

page1 of 1

Tel: +86 10 83886666

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

型号	输出端口	最大输入功率 (Max.W)	输出参数			
			输出电流 (mA)	输出电压 (Vdc)	最大空载电压 (Max.Vdc)	备注
LS-7/12-150/220 SI	150mA 输出端 口	8.1	150	27-42	55	- 两组输出
	220mA 输出端 口	11.9	220	27-42	55	

输入: 220-240V~ 50/60Hz

