



Page 1/2



NO4703

Order No.

431817

Licence for use of the here shown ENEC conformity mark :



Based on:

Agreement on the use of a commonly agreed Mark on Conformity for equipment complying with European Standards as of 12 November 1991 (in short ENEC Agreement), as revised latest by ENEC group April 16. 1997.

Nemko hereby grants the following manufacturer as licensee the right to affix this ENEC mark on the product(s) specified below.

ProductLED Power SupplyApplicantEaglerise Electric & Electronic (China) Co., Ltd. No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong Province ChinaManufacturerEaglerise Electric & Electronic (China) Co., Ltd. No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong Province ChinaFactorySee page 2RatingsPRI: max. 0.12 A, 220-240 V~, 50/60 Hz, PF = 0.8C/0.85C; SEC: 5.0-14.0 W, max. 0.70 A, 7-48 V d.c. (under load), max. 55 V d.c. (no-load)Trade markCS-8-XXX MB, CS-12-XXX MB Built-in LED Power Supply with double or reinforced insulation, constant current output, thermal protected 110 °C, providing SELV output, ta: 60 °C, to: 90 °C The XXX' is for the output current and represents the number is 120 mA, 150 mA, 180 mA 200 mA. for CS-8-XXX MB only) or from 250 mA to 700 mA, 150 mA, 180 mA 200 mA. For example, 700 means the output current is r00 mA.		
No.Ã3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong Province ChinaManufacturerEaglerise Electric & Electronic (China) Co., Ltd. No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong Province ChinaFactorySee page 2RatingsPRI: max. 0.12 A, 220-240 V~, 50/60 Hz, PF = 0.8C/0.85C; SEC: 5.0-14.0 W, max. 0.70 A, 7-48 V d.c. (under load), max. 55 V d.c. (no-load)Trade markCS-8-XXX MB, CS-12-XXX MBModel / Type Ref.CS-8-XXX MB, CS-12-XXX MBPrincipal characteristicsBuilt-in LED Power Supply with double or reinforced insulation, constant current output, thermal protected 110 °C, providing SELV output, ta: 60 °C, tc: 90 °C The 'XXY' is for the output current and represents the number is 120 mA, 150 mA, 180 mA 200 mA (for CS-8-XXX MB only) or from 250 mA to 700 mA (for both models) in step of 50 mA. For example, 700 means the output current is 700 mA.	Product	LED Power Supply
Road, Nanhai District, Foshan City, Guangdong Province ChinaManufacturerEaglerise Electric & Electronic (China) Co., Ltd. No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong Province ChinaFactorySee page 2RatingsPRI: max. 0.12 A, 220-240 V~, 50/60 Hz, PF = 0.8C/0.85C; SEC: 5.0-14.0 W, max. 0.70 A, 7-48 V d.c. (under load), max. 55 V d.c. (no-load)Trade markEAGLECRISEModel / Type Ref.CS-8-XXX MB, CS-12-XXX MB Built-in LED Power Supply with double or reinforced insulation, constant current output, thermal protected 110 °C, providing SELV output, ta: 60 °C, to: 90 °C The 'XXX' is for the output current and represents the number is 120 mA, 150 mA, 180 mA 200 mA (for CS-8-XXX MB only) or from 250 mA to 700 mA (for both models) in step of 50 mA. For example, 700 means the output current is 700 mA.	Applicant	
ManufacturerChinaManufacturerEaglerise Electric & Electronic (China) Co., Ltd. No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong Province ChinaFactoryIsee page 2RatingsPRI: max. 0.12 A, 220-240 V~, 50/60 Hz, PF = 0.8C/0.85C; SEC: 5.0-14.0 W, max. 0.70 A, 7-48 V d.c. (under load), max. 55 V d.c. (no-load)Trade markImage: CS-8-XXX MB, CS-12-XXX MB Built-in LED Power Supply with double or reinforced insulation, constant current output, thermal protected 110 °C, providing SELV output, ta: 60 °C, tc: 90 °C The 'XXX' is for the output current and represents the number is 120 mA, 150 mA, 180 mA 200 mA (for CS-8-XXX MB only) or from 250 mA to 700 mA (for both models) in step of 50 mA. For example, 700 means the output current is 700 mA.		
ManufacturerEaglerise Electric & Electronic (China) Co., Ltd. No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong Province ChinaFactory✓ See page 2Ratings✓ See page 2RatingsPRI: max. 0.12 A, 220-240 V~, 50/60 Hz, PF = 0.8C/0.85C; SEC: 5.0-14.0 W, max. 0.70 A, 7-48 V d.c. (under load), max. 55 V d.c. (no-load)Trade mark✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓		
No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong Province China Factory ✓ See page 2 Ratings PRI: max. 0.12 A, 220-240 V~, 50/60 Hz, PF = 0.8C/0.85C; SEC: 5.0-14.0 W, max. 0.70 A, 7-48 V d.c. (under load), max. 55 V d.c. (no-load) Trade mark ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓	Manufacturer	
Factory ✓ See page 2 Ratings PRI: max. 0.12 A, 220-240 V~, 50/60 Hz, PF = 0.8C/0.85C; SEC: 5.0-14.0 W, max. 0.70 A, 7-48 V d.c. (under load), max. 55 V d.c. (no-load) Trade mark ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓	Manalaction	
Factory RatingsSee page 2RatingsPRI: max. 0.12 A, 220-240 V~, 50/60 Hz, PF = 0.8C/0.85C; SEC: 5.0-14.0 W, max. 0.70 A, 7-48 V d.c. (under load), max. 55 V d.c. (no-load)Trade markCS-8-XXX MB, CS-12-XXX MBModel / Type Ref.CS-8-XXX MB, CS-12-XXX MBPrincipal characteristicsSult-in LED Power Supply with double or reinforced insulation, constant current output, thermal protected 110 °C, providing SELV output, ta: 60 °C, tc: 90 °C The 'XXX' is for the output current and represents the number is 120 mA, 150 mA, 180 mA 200 mA (for CS-8-XXX MB only) or from 250 mA to 700 mA (for both models) in step of 50 mA. For example, 700 means the output current is 700 mA.		
RatingsPRI: max. 0.12 A, 220-240 V~, 50/60 Hz, PF = 0.8C/0.85C; SEC: 5.0-14.0 W, max. 0.70 A, 7-48 V d.c. (under load), max. 55 V d.c. (no-load)Trade mark EAGLERISE Model / Type Ref.CS-8-XXX MB, CS-12-XXX MBPrincipal characteristicsBuilt-in LED Power Supply with double or reinforced insulation, constant current output, thermal protected 110 °C, providing SELV output, ta: 60 °C, tc: 90 °C The 'XXX' is for the output current and represents the number is 120 mA, 150 mA, 180 mA 200 mA (for CS-8-XXX MB only) or from 250 mA to 700 mA (for both models) in step of 50 mA. For example, 700 means the output current is 700 mA.		
SEC: 5.0-14.0 W, max. 0.70 A, 7-48 V d.c. (under load), max. 55 V d.c. (no-load)Trade markEAGLERISEModel / Type Ref. Principal characteristicsCS-8-XXX MB, CS-12-XXX MB Built-in LED Power Supply with double or reinforced insulation, constant current output, thermal protected 110 °C, providing SELV output, ta: 60 °C, tc: 90 °C The 'XXX' is for the output current and represents the number is 120 mA, 150 mA, 180 mA 200 mA (for CS-8-XXX MB only) or from 250 mA to 700 mA (for both models) in step of 50 mA. For example, 700 means the output current is 700 mA.	-	
Trade markmax. 55 V d.c. (no-load)Model / Type Ref.Frincipal characteristicsPrincipal characteristicsCS-8-XXX MB, CS-12-XXX MB Built-in LED Power Supply with double or reinforced insulation, constant current output, thermal protected 110 °C, providing SELV output, ta: 60 °C, tc: 90 °C The 'XXX' is for the output current and represents the number is 120 mA, 150 mA, 180 mA 200 mA (for CS-8-XXX MB only) or from 250 mA to 700 mA (for both models) in step of 50 mA. For example, 700 means the output current is 700 mA.	Ratings	
Trade mark Find the second		
Model / Type Ref.CS-8-XXX MB, CS-12-XXX MBPrincipal characteristicsCS-8-XXX MB, CS-12-XXX MBBuilt-in LED Power Supply with double or reinforced insulation, constant current output, thermal protected 110 °C, providing SELV output, ta: 60 °C, tc: 90 °CThe 'XXX' is for the output current and represents the number is 120 mA, 150 mA, 180 mA 200 mA (for CS-8-XXX MB only) or from 250 mA to 700 mA (for both models) in step of 50 mA. For example, 700 means the output current is 700 mA.	Trada mark	
Model / Type Ref.CS-8-XXX MB, CS-12-XXX MBPrincipal characteristicsBuilt-in LED Power Supply with double or reinforced insulation, constant current output, thermal protected 110 °C, providing SELV output, ta: 60 °C, tc: 90 °CThe 'XXX' is for the output current and represents the number is 120 mA, 150 mA, 180 mA 200 mA (for CS-8-XXX MB only) or from 250 mA to 700 mA (for both models) in step of 50 mA. For example, 700 means the output current is 700 mA.	Trade mark	\leq \checkmark
Model / Type Ref.CS-8-XXX MB, CS-12-XXX MBPrincipal characteristicsBuilt-in LED Power Supply with double or reinforced insulation, constant current output, thermal protected 110 °C, providing SELV output, ta: 60 °C, tc: 90 °CThe 'XXX' is for the output current and represents the number is 120 mA, 150 mA, 180 mA 200 mA (for CS-8-XXX MB only) or from 250 mA to 700 mA (for both models) in step of 50 mA. For example, 700 means the output current is 700 mA.		
Principal characteristicsBuilt-in LED Power Supply with double or reinforced insulation, constant current output, thermal protected 110 °C, providing SELV output, ta: 60 °C, tc: 90 °C The 'XXX' is for the output current and represents the number is 120 mA, 150 mA, 180 mA 200 mA (for CS-8-XXX MB only) or from 250 mA to 700 mA (for both models) in step of 50 mA. For example, 700 means the output current is 700 mA.		
constant current output, thermal protected 110 °C, providing SELV output, ta: 60 °C, tc: 90 °C The 'XXX' is for the output current and represents the number is 120 mA, 150 mA, 180 mA 200 mA (for CS-8-XXX MB only) or from 250 mA to 700 mA (for both models) in step of 50 mA. For example, 700 means the output current is 700 mA.	Model / Type Ref.	CS-8-XXX MB, CS-12-XXX MB
providing SELV output, ta: 60 °C, tc: 90 °C The 'XXX' is for the output current and represents the number is 120 mA, 150 mA, 180 mA 200 mA (for CS-8-XXX MB only) or from 250 mA to 700 mA (for both models) in step of 50 mA. For example, 700 means the output current is 700 mA.	Principal characteristics	Built-in LED Power Supply with double or reinforced insulation,
The 'XXX' is for the output current and represents the number is 120 mA, 150 mA, 180 mA 200 mA (for CS-8-XXX MB only) or from 250 mA to 700 mA (for both models) in step of 50 mA. For example, 700 means the output current is 700 mA.		constant current output, thermal protected 110 °C,
mA, 180 mA 200 mA (for CS-8-XXX MB only) or from 250 mA to 700 mA (for both models) in step of 50 mA. For example, 700 means the output current is 700 mA.		
both models) in step of 50 mA. For example, 700 means the output current is 700 mA.		
700 mA.		
		\Box See next page(s)
A sample of the product was tested LITE EN 61347-1:2015		
and found to be in conformity with EN 61347-2-13:2014;A1 EN 62384:2006;A1	and found to be in conformity with	,
The conditions for this licence are that the ENEC-marked products conform with the applicable Standard(s) as stated in		
the Test Report with Order No: 431817		
and that Articles 8 and 9 of the ENEC Agreement are fulfilled by the manufacturer. The mark signifies the compliance of the		

completed products with these conditions. Further information is given in the attached Annex, which forms an obligatory part of this licence document. This licence has been issued under the presumption and conditional on the fact that the licensee holds all necessary legal rights with regard to the product presented for testing and certification.

Additional model(s)

See next page(s)

Date of issue 28-04-2021

aīm

Jiyea Gim Certification Department

Nemko AS Philip Pedersens vei 11, 1366 Lysaker, Norway TEL +47 22 96 03 30 EMAIL info@nemko.com ENTERPRISE NUMBER NO974404532







NO4703

Page 2/2 Order No.

431817

Licence for use of the here shown ENEC conformity mark :



Factories:

China

Co., Ltd. No.4, East Huanzhen Road, Beijiao Shunde Foshan, Guangdong 528000

Foshan Eaglerise Power Science & Technology(Shunde) EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD West Zone, Ji an County Industrial Park, Ji an County Jiangxi Province China

Date of issue 28-04-2021

ิสโฑ

Jiyea Gim Certification Department

Nemko AS Philip Pedersens vei 11, 1366 Lysaker, Norway TEL +47 22 96 03 30 EMAIL info@nemko.com ENTERPRISE NUMBER NO974404532