

CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2023011002567542		Valid from: Aug.29,2023		
		Valid until:May.03,2028		
NAME AND REGISTERED ADDRESS OF THE APPLICANT	Eaglerise Electric & Electronic (China) Co., Ltd No.A3, Guicheng Sci-Tech Industrial Park, Jiar Province, P.R.China	Iping Road, Nanhai District, Foshan City, Guangdong		
NAME AND REGISTERED ADDRESS OF THE MANUFACTURER	Eaglerise Electric & Electronic (China) Co., Ltd No.A3, Guicheng Sci-Tech Industrial Park, Jia Province, P.R.China	nping Road, Nanhai District, Foshan City, Guangdong		
NAME AND LOCATION OF THE FACTORY		Road And Chaoyang Road, Industrial Park, Ji An County,		
	Jiangxi Province, P.R.China			
PRODUCT MODEL(S)	A.C. Supplied Electronic Controlgear For LED	Modules (Independent, Constant Voltage Mode, SELV,		
	IP20, Class Ⅱ, Non-dimmable, ta: 45 ℃, tc:75	/90°C, Suitable For Direct Mounting On Normally		
	Flammable Material, Temperature Declared T See Appendix; 220-240V~ 50/60Hz.	hermally Protected: 110°C)		
STANDARDS AND TECHNICAL REQUIREMENTS	GB 17625.1-2022;GB/T 17743-2021;GB 19510	.1-2009;GB 19510.14-2009		

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C10-01:2014)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn





SIGNATURE: 谢肇煦

) CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2023011002567542

page1of 1

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

	输出参数				
型号	输出电流 (Max.A)	恒定输出 电压(Vdc)	输出功率 Max.(W)	ta(℃)	tc(°C)
LS-30-12 LI EXC	2.5	12	30	45	75
LS-30-24 LI EXC	1.25	24	30	45	75
LS-60-12 LI EXC	5.0	12	60	45	90
LS-60-24 LI EXC	2.5	24	60	45	90
LS-75-12 LI EXC	6.25	12	75	45	90
LS-75-24 LI EXC	3.13	24	75	45	90

输入:220-240V~ 50/60Hz

