



Ref. Certif. No

NO127765

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

LED Power Supply

Name and address of the applicant

Foshan Eaglerise Power Science & Technology (Shunde) Co., Ltd.
No.4, East Huanzhen Road, Beijiao Shunde, Foshan, Guangdong
China

Name and address of the manufacturer

Foshan Eaglerise Power Science & Technology (Shunde) Co., Ltd.
No.4, East Huanzhen Road, Beijiao Shunde, Foshan, Guangdong
China

Name and address of the factory

See next page(s)

Note: When more than one factory, please report on page 2

 Additional Information on Page 2

Ratings and Principal characteristics

PRI: max. 0.39 A, 220-240 V~, 50/60 Hz
SEC: max.50.4 W, max. 1.2 A, 12-85 V (under load), max. 105 V d.c. (no-load), Cl. II

Trademark /Brand (If any)



Customer's Testing Facility (CTF) Stage used

Model/Type Ref

LS-xx-yyyy TRIAC LI, LS-40-yyyy RI1

Additional information (If necessary may also be reported on Page 2)

 Additional Information on Page 2

A sample of the product was tested and found to be in conformity with

IEC 61347-1:2015, IEC 61347-1:2015/AMD1:2017
IEC 61347-2-13:2014, IEC 61347-2-13:2014/AMD1:2016

As shown in the Test Report Ref. No. which forms part of this Certificate

REP015733

This CB Test Certificate is issued by the National Certification Body

Philip Pedersen vei 11,
NO-1366 Lysaker, Norway

Date: 08-09-2023

Signature: Juan Z Saussey
Certification department



Ref. Certif. No

NO127765

Foshan Eaglerise Power Science & Technology (Shunde) Co., Ltd.
No.4, East Huanzhen Road, Beijiao Shunde, Foshan, Guangdong
China

EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD
West Zone, Ji An County Industrial Park, Ji an County
Jiangxi Province
China

Additional Information (if necessary)

IP20, constant current output, thermal protected 110 °C,
ta: 45 °C / 50 °C, tc: 70 °C / 75 °C / 80 °C / 85 °C, Independent controlgear providing SELV output.

LS-xx-yyyy TRIAC LI:

The 'xx' in the type designation can be 6, 9, 12, 15, 20, 30, 40 or 50, indicating the approximate rated output wattage in Watt.

The 'yyyy' can be 150 to 1200 by the step of 50, indicating the output current in mA.

LS-40-yyyy RI1:

The 'yyyy' can be 700 to 1050 by the step of 50, indicating the output current in mA.

For example, 700 means the output current is 700 mA, 1050 means the output current is 1050 mA.



Philip Pedersen vei 11,
NO-1366 Lysaker, Norway

Date: 08-09-2023

Signature: Juan Z Saussey
Certification department