



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2022011002479573

Valid from: Sep.21,2023

Valid until:May.15,2027

NAME AND REGISTERED ADDRESS OF THE APPLICANT	Eaglerise Electric & Electronic (China) Co., Ltd. No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong Province, P.R.China
NAME AND REGISTERED ADDRESS OF THE MANUFACTURER	Eaglerise Electric & Electronic (China) Co., Ltd. No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong Province, P.R.China
NAME AND LOCATION OF THE FACTORY	Eaglerise Electric & Electronic (Ji An) Co., Ltd. Southwest Corner, Crossing Between Panlong Road And Chaoyang Road, Industrial Park, Ji An County, Jiangxi Province, P.R.China
PRODUCT MODEL(S)	A.C. Supplied Electronic Controlgear For LED Modules (Independent, Constant Current Mode, SELV,Non-dimmable, ta:40/45/50/55°C, tc:70/75/80°C, Class II, IP20, Suitable For Direct Mounting On Normally Flammable Material, Temperature Declared Thermally Protected: 110°C) See Appendix;220-240V ~ 50/60Hz.
STANDARDS AND TECHNICAL REQUIREMENTS	GB 17625.1-2022;GB/T 17743-2021;GB 19510.1-2009;GB 19510.14-2009

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C10-01:2014)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Date of original issued: Jun.27,2022

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2022011002479573

page 1 of 8

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

序号	型号	输入			输出				ta (°C)	tc (°C)
		电压 (V~)	最大 电流 (A)	频率 (Hz)	恒流 (mA)	工作电压 (Vdc)	最大输出 电压 (Vdc)	最大功 率 (W)		
1.	LS-8-120 SI ECO	220-240	0.08	50/60	120	30-42	59	5.1	45	70
2.	LS-8-150 SI ECO	220-240	0.09	50/60	150	30-42	59	6.3	45	70
3.	LS-8-180 SI ECO	220-240	0.11	50/60	180	30-42	59	7.6	45	70
4.	LS-8-200 SI ECO	220-240	0.12	50/60	200	30-42	59	8.4	45	70
5.	LS-8-250 SI ECO	220-240	0.1	50/60	250	16-26	37	6.5	45	70
6.	LS-8-300 SI ECO	220-240	0.1	50/60	300	15-24	40	7.2	45	70
7.	LS-8-350 SI ECO	220-240	0.12	50/60	350	15-24	35	8.4	45	70
8.	LS-8-400 SI ECO	220-240	0.12	50/60	400	12-20	30	8	45	70
9.	LS-8-450 SI ECO	220-240	0.12	50/60	450	11-18	30	8.1	45	70
10.	LS-8-500 SI ECO	220-240	0.12	50/60	500	10-16	26	8	45	70
11.	LS-8-550 SI ECO	220-240	0.12	50/60	550	9-14	25	7.7	45	70
12.	LS-8-600 SI ECO	220-240	0.12	50/60	600	8-13	25	7.8	45	70
13.	LS-12-250 SI ECO	220-240	0.15	50/60	250	30-42	59	10.5	45	70
14.	LS-12-300 SI ECO	220-240	0.18	50/60	300	30-42	59	12.6	45	70
15.	LS-12-350 SI ECO	220-240	0.2	50/60	350	27-40	57	14	45	70
16.	LS-12-400 SI ECO	220-240	0.18	50/60	400	20-30	45	12	45	70
17.	LS-12-450 SI ECO	220-240	0.18	50/60	450	16-26	39	11.7	45	70
18.	LS-12-500 SI ECO	220-240	0.19	50/60	500	14-26	39	13	45	70
19.	LS-12-550 SI ECO	220-240	0.19	50/60	550	12-21	32	11.6	45	70
20.	LS-12-600 SI ECO	220-240	0.19	50/60	600	11-20	31	12	45	70
21.	LS-21-300 SI ECO	220-240	0.3	50/60	300	50-70	90	21	45	80
22.	LS-21-350 SI ECO	220-240	0.3	50/60	350	42-60	80	21	45	80
23.	LS-21-400 SI ECO	220-240	0.3	50/60	400	27-42	55	16.8	45	80



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2022011002479573

page2of 8

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

序号	型号	输入			输出				ta (°C)	tc (°C)
		电压 (V~)	最大 电流 (A)	频率 (Hz)	恒流 (mA)	工作电压 (Vdc)	最大输出 电压 (Vdc)	最大功 率 (W)		
24.	LS-21-450 SI ECO	220-240	0.3	50/60	450	27-42	55	18.9	45	80
25.	LS-21-500 SI ECO	220-240	0.3	50/60	500	27-42	55	21	45	80
26.	LS-21-550 SI ECO	220-240	0.3	50/60	550	27-40	55	22	45	80
27.	LS-21-600 SI ECO	220-240	0.3	50/60	600	27-39	55	23.4	45	80
28.	LS-21-650 SI ECO	220-240	0.3	50/60	650	20-32	50	20.8	45	80
29.	LS-21-700 SI ECO	220-240	0.3	50/60	700	18-30	50	21	45	80
30.	LS-8-220 SI ECO	220-240	0.07	50/60	220	30-38.5	50	8.5	45	70
31.	LS-6-120 SI ECO	220-240	0.11	50/60	120	27-40	59	4.8	50	80
32.	LS-6-150 SI ECO	220-240	0.11	50/60	150	27-40	59	6	50	80
33.	LS-6-180 SI ECO	220-240	0.11	50/60	180	27-40	59	7.2	50	80
34.	LS-6-200 SI ECO	220-240	0.11	50/60	200	27-40	59	8	50	80
35.	LS-6-250 SI ECO	220-240	0.11	50/60	250	10-24	45	6	50	80
36.	LS-6-300 SI ECO	220-240	0.11	50/60	300	8-20	40	6	50	80
37.	LS-6-350 SI ECO	220-240	0.11	50/60	350	8-18	40	6.3	50	80
38.	LS-6-400 SI ECO	220-240	0.11	50/60	400	5-15	30	6	50	80
39.	LS-6-450 SI ECO	220-240	0.11	50/60	450	5-13.5	30	6.1	50	80
40.	LS-6-500 SI ECO	220-240	0.11	50/60	500	5-12	30	6	50	80
41.	LS-6-550 SI ECO	220-240	0.11	50/60	550	5-11	30	6.05	50	80
42.	LS-6-600 SI ECO	220-240	0.11	50/60	600	4-9	25	5.4	50	80
43.	LS-6-650 SI ECO	220-240	0.11	50/60	650	4-9	25	5.85	50	80
44.	LS-6-700 SI ECO	220-240	0.11	50/60	700	4-9	25	6.3	50	80
45.	LS-6-120 SI E	220-240	0.11	50/60	120	27-40	59	4.8	50	80
46.	LS-6-150 SI E	220-240	0.11	50/60	150	27-40	59	6	50	80
47.	LS-6-180 SI E	220-240	0.11	50/60	180	27-40	59	7.2	50	80
48.	LS-6-200 SI E	220-240	0.11	50/60	200	27-40	59	8	50	80



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2022011002479573

page3of 8

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

序号	型号	输入			输出				ta (°C)	tc (°C)
		电压 (V~)	最大 电流 (A)	频率 (Hz)	恒流 (mA)	工作电压 (Vdc)	最大输出 电压 (Vdc)	最大功 率 (W)		
49.	LS-6-250 SI E	220-240	0.11	50/60	250	10-24	45	6	50	80
50.	LS-6-300 SI E	220-240	0.11	50/60	300	8-20	40	6	50	80
51.	LS-6-350 SI E	220-240	0.11	50/60	350	8-18	40	6.3	50	80
52.	LS-6-400 SI E	220-240	0.11	50/60	400	5-15	30	6	50	80
53.	LS-6-450 SI E	220-240	0.11	50/60	450	5-13.5	30	6.1	50	80
54.	LS-6-500 SI E	220-240	0.11	50/60	500	5-12	30	6	50	80
55.	LS-6-550 SI E	220-240	0.11	50/60	550	5-11	30	6.05	50	80
56.	LS-6-600 SI E	220-240	0.11	50/60	600	4-9	25	5.4	50	80
57.	LS-6-650 SI E	220-240	0.11	50/60	650	4-9	25	5.85	50	80
58.	LS-6-700 SI E	220-240	0.11	50/60	700	4-9	25	6.3	50	80
59.	LS-8-120 LI EXC	220-240	0.07	50/60	120	27-50	59	6	55	75
60.	LS-8-150 LI EXC	220-240	0.07	50/60	150	27-50	59	7.5	55	75
61.	LS-8-180 LI EXC	220-240	0.07	50/60	180	22-42	55	7.6	55	75
62.	LS-8-200 LI EXC	220-240	0.07	50/60	200	22-42	55	8.4	55	75
63.	LS-8-220 LI EXC	220-240	0.07	50/60	220	22-42	55	9.24	55	75
64.	LS-8-250 LI EXC	220-240	0.07	50/60	250	14-27	45	6.75	55	75
65.	LS-8-300 LI EXC	220-240	0.07	50/60	300	14-27	45	8.1	55	75
66.	LS-8-350 LI EXC	220-240	0.07	50/60	350	12-24	35	8.4	55	75
67.	LS-12-250 LI EXC	220-240	0.09	50/60	250	24-42	55	10.5	45	75
68.	LS-12-300 LI EXC	220-240	0.09	50/60	300	24-42	55	12.6	45	75
69.	LS-12-350 LI EXC	220-240	0.09	50/60	350	24-40	55	14	45	75
70.	LS-20-350 LI EXC	220-240	0.16	50/60	350	40-60	75	21	45	80
71.	LS-20-400 LI EXC	220-240	0.16	50/60	400	24-42	55	16.8	45	80
72.	LS-20-450 LI EXC	220-240	0.16	50/60	450	24-42	55	18.9	45	80
73.	LS-20-500 LI EXC	220-240	0.16	50/60	500	24-42	55	21	45	80



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2022011002479573

page4of 8

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

序号	型号	输入			输出				ta (°C)	tc (°C)
		电压 (V~)	最大 电流 (A)	频率 (Hz)	恒流 (mA)	工作电压 (Vdc)	最大输出 电压 (Vdc)	最大功 率 (W)		
74.	LS-20-550 LI EXC	220-240	0.16	50/60	550	24-40	55	22	45	80
75.	LS-20-600 LI EXC	220-240	0.16	50/60	600	24-40	55	24	45	80
76.	LS-20-700 LI EXC	220-240	0.16	50/60	700	18-30	45	21	45	80
77.	LS-21-250 SI1 ECO	220-240	0.3	50/60	250	50-80	95	20	45	80
78.	LS-21-300 SI1 ECO	220-240	0.3	50/60	300	40-70	90	21	45	80
79.	LS-21-350 SI1 ECO	220-240	0.3	50/60	350	42-60	80	21	45	80
80.	LS-21-400 SI1 ECO	220-240	0.3	50/60	400	27-42	55	16.8	45	80
81.	LS-21-450 SI1 ECO	220-240	0.3	50/60	450	27-42	55	18.9	45	80
82.	LS-21-500 SI1 ECO	220-240	0.3	50/60	500	27-42	55	21	45	80
83.	LS-21-550 SI1 ECO	220-240	0.3	50/60	550	27-40	55	22	45	80
84.	LS-21-600 SI1 ECO	220-240	0.3	50/60	600	27-39	55	23.4	45	80
85.	LS-21-650 SI1 ECO	220-240	0.3	50/60	650	20-32	50	20.8	45	80
86.	LS-21-700 SI1 ECO	220-240	0.3	50/60	700	18-30	50	21	45	80
87.	LS-8-120 SI1 ECO	220-240	0.08	50/60	120	30-42	59	5.1	45	70
88.	LS-8-150 SI1 ECO	220-240	0.09	50/60	150	30-42	59	6.3	45	70
89.	LS-8-180 SI1 ECO	220-240	0.11	50/60	180	30-42	59	7.6	45	70
90.	LS-8-200 SI1 ECO	220-240	0.12	50/60	200	30-42	59	8.4	45	70
91.	LS-8-220 SI1 ECO	220-240	0.07	50/60	220	30-38.5	59	8.5	45	70
92.	LS-8-250 SI1 ECO	220-240	0.1	50/60	250	16-26	42	6.5	45	70
93.	LS-8-300 SI1 ECO	220-240	0.1	50/60	300	15-24	40	7.2	45	70
94.	LS-8-350 SI1 ECO	220-240	0.12	50/60	350	15-24	40	8.4	45	70
95.	LS-8-400 SI1 ECO	220-240	0.12	50/60	400	12-20	35	8	45	70
96.	LS-8-450 SI1 ECO	220-240	0.12	50/60	450	11-18	32	8.1	45	70
97.	LS-8-500 SI1 ECO	220-240	0.12	50/60	500	10-16	26	8	45	70
98.	LS-8-550 SI1 ECO	220-240	0.12	50/60	550	9-14	25	7.7	45	70



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2022011002479573

page5of 8

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

序号	型号	输入			输出				ta (°C)	tc (°C)
		电压 (V~)	最大 电流 (A)	频率 (Hz)	恒流 (mA)	工作电压 (Vdc)	最大输出 电压 (Vdc)	最大功 率 (W)		
99.	LS-8-600 SI1 ECO	220-240	0.12	50/60	600	8-13	25	7.8	45	70
100.	LS-12-250 SI1 ECO	220-240	0.15	50/60	250	30-42	59	10.5	45	70
101.	LS-12-300 SI1 ECO	220-240	0.18	50/60	300	30-42	59	12.6	45	70
102.	LS-12-350 SI1 ECO	220-240	0.2	50/60	350	27-40	57	14	45	70
103.	LS-12-400 SI1 ECO	220-240	0.18	50/60	400	20-30	45	12	45	70
104.	LS-12-450 SI1 ECO	220-240	0.18	50/60	450	16-26	42	11.7	45	70
105.	LS-12-500 SI1 ECO	220-240	0.19	50/60	500	14-26	42	13	45	70
106.	LS-12-550 SI1 ECO	220-240	0.19	50/60	550	12-21	35	11.6	45	70
107.	LS-12-600 SI1 ECO	220-240	0.19	50/60	600	11-20	35	12	45	70
108.	LS-21-250 SI1 E	220-240	0.3	50/60	250	50-80	95	20	45	80
109.	LS-21-300 SI1 E	220-240	0.3	50/60	300	40-70	90	21	45	80
110.	LS-21-350 SI1 E	220-240	0.3	50/60	350	42-60	80	21	45	80
111.	LS-21-400 SI1 E	220-240	0.3	50/60	400	27-42	55	16.8	45	80
112.	LS-21-450 SI1 E	220-240	0.3	50/60	450	27-42	55	18.9	45	80
113.	LS-21-500 SI1 E	220-240	0.3	50/60	500	27-42	55	21	45	80
114.	LS-21-550 SI1 E	220-240	0.3	50/60	550	27-40	55	22	45	80
115.	LS-21-600 SI1 E	220-240	0.3	50/60	600	27-39	55	23.4	45	80
116.	LS-21-650 SI1 E	220-240	0.3	50/60	650	20-32	50	20.8	45	80
117.	LS-21-700 SI1 E	220-240	0.3	50/60	700	18-30	50	21	45	80
118.	LS-8-120 SI1 E	220-240	0.08	50/60	120	30-42	59	5.1	45	70
119.	LS-8-150 SI1 E	220-240	0.09	50/60	150	30-42	59	6.3	45	70
120.	LS-8-180 SI1 E	220-240	0.11	50/60	180	30-42	59	7.6	45	70
121.	LS-8-200 SI1 E	220-240	0.12	50/60	200	30-42	59	8.4	45	70
122.	LS-8-220 SI1 E	220-240	0.07	50/60	220	30-38.5	59	8.5	45	70
123.	LS-8-250 SI1 E	220-240	0.1	50/60	250	16-26	42	6.5	45	70



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2022011002479573

page 6 of 8

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

序号	型号	输入			输出				ta (°C)	tc (°C)
		电压 (V~)	最大 电流 (A)	频率 (Hz)	恒流 (mA)	工作电压 (Vdc)	最大输出 电压 (Vdc)	最大功 率 (W)		
124.	LS-8-300 SI1 E	220-240	0.1	50/60	300	15-24	40	7.2	45	70
125.	LS-8-350 SI1 E	220-240	0.12	50/60	350	15-24	40	8.4	45	70
126.	LS-8-400 SI1 E	220-240	0.12	50/60	400	12-20	35	8	45	70
127.	LS-8-450 SI1 E	220-240	0.12	50/60	450	11-18	32	8.1	45	70
128.	LS-8-500 SI1 E	220-240	0.12	50/60	500	10-16	26	8	45	70
129.	LS-8-550 SI1 E	220-240	0.12	50/60	550	9-14	25	7.7	45	70
130.	LS-8-600 SI1 E	220-240	0.12	50/60	600	8-13	25	7.8	45	70
131.	LS-12-250 SI1 E	220-240	0.15	50/60	250	30-42	59	10.5	45	70
132.	LS-12-300 SI1 E	220-240	0.18	50/60	300	30-42	59	12.6	45	70
133.	LS-12-350 SI1 E	220-240	0.2	50/60	350	27-40	57	14	45	70
134.	LS-12-400 SI1 E	220-240	0.18	50/60	400	20-30	45	12	45	70
135.	LS-12-450 SI1 E	220-240	0.18	50/60	450	16-26	42	11.7	45	70
136.	LS-12-500 SI1 E	220-240	0.19	50/60	500	14-26	42	13	45	70
137.	LS-12-550 SI1 E	220-240	0.19	50/60	550	12-21	35	11.6	45	70
138.	LS-12-600 SI1 E	220-240	0.19	50/60	600	11-20	35	12	45	70
139.	LS-8-120 SI E	220-240	0.08	50/60	120	30-42	59	5.1	45	70
140.	LS-8-150 SI E	220-240	0.09	50/60	150	30-42	59	6.3	45	70
141.	LS-8-180 SI E	220-240	0.11	50/60	180	30-42	59	7.6	45	70
142.	LS-8-200 SI E	220-240	0.12	50/60	200	30-42	59	8.4	45	70
143.	LS-8-220 SI E	220-240	0.07	50/60	220	30-38.5	50	8.5	45	70
144.	LS-8-250 SI E	220-240	0.1	50/60	250	16-26	37	6.5	45	70
145.	LS-8-300 SI E	220-240	0.1	50/60	300	15-24	40	7.2	45	70
146.	LS-8-350 SI E	220-240	0.12	50/60	350	15-24	35	8.4	45	70
147.	LS-8-400 SI E	220-240	0.12	50/60	400	12-20	30	8	45	70
148.	LS-8-450 SI E	220-240	0.12	50/60	450	11-18	30	8.1	45	70



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2022011002479573

page7of 8

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

序号	型号	输入			输出				ta (°C)	tc (°C)
		电压 (V~)	最大 电流 (A)	频率 (Hz)	恒流 (mA)	工作电压 (Vdc)	最大输出 电压 (Vdc)	最大功 率 (W)		
149.	LS-8-500 SI E	220-240	0.12	50/60	500	10-16	26	8	45	70
150.	LS-8-550 SI E	220-240	0.12	50/60	550	9-14	25	7.7	45	70
151.	LS-8-600 SI E	220-240	0.12	50/60	600	8-13	25	7.8	45	70
152.	LS-12-250 SI E	220-240	0.15	50/60	250	30-42	59	10.5	45	70
153.	LS-12-300 SI E	220-240	0.18	50/60	300	30-42	59	12.6	45	70
154.	LS-12-350 SI E	220-240	0.2	50/60	350	27-40	57	14	45	70
155.	LS-12-400 SI E	220-240	0.18	50/60	400	20-30	45	12	45	70
156.	LS-12-450 SI E	220-240	0.18	50/60	450	16-26	39	11.7	45	70
157.	LS-12-500 SI E	220-240	0.19	50/60	500	14-26	39	13	45	70
158.	LS-12-550 SI E	220-240	0.19	50/60	550	12-21	32	11.6	45	70
159.	LS-12-600 SI E	220-240	0.19	50/60	600	11-20	31	12	45	70
160.	LS-21-300 SI E	220-240	0.3	50/60	300	50-70	90	21	45	80
161.	LS-21-350 SI E	220-240	0.3	50/60	350	42-60	80	21	45	80
162.	LS-21-400 SI E	220-240	0.3	50/60	400	27-42	55	16.8	45	80
163.	LS-21-450 SI E	220-240	0.3	50/60	450	27-42	55	18.9	45	80
164.	LS-21-500 SI E	220-240	0.3	50/60	500	27-42	55	21	45	80
165.	LS-21-550 SI E	220-240	0.3	50/60	550	27-40	55	22	45	80
166.	LS-21-600 SI E	220-240	0.3	50/60	600	27-39	55	23.4	45	80
167.	LS-21-650 SI E	220-240	0.3	50/60	650	20-32	50	20.8	45	80
168.	LS-21-700 SI E	220-240	0.3	50/60	700	18-30	50	21	45	80
169.	LS-8-180 SI E1	220-240	0.11	50/60	180	30-42	59	7.56	45	80
170.	LS-8-200 SI E1	220-240	0.11	50/60	200	30-42	59	8.4	45	80
171.	LS-8-220 SI E1	220-240	0.11	50/60	220	30-42	59	9.24	45	80
172.	LS-8-700 SI E1	220-240	0.11	50/60	700	8-13	24	9.1	40	80
173.	LS-6-220 SI ECO	220-240	0.11	50/60	220	27-40	59	8.8	50	80



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2022011002479573

page8of 8

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

序号	型号	输入			输出			ta (°C)	tc (°C)	
		电压 (V~)	最大 电流 (A)	频率 (Hz)	恒流 (mA)	工作电压 (Vdc)	最大输出 电压 (Vdc)			最大功 率 (W)
174.	LS-6-220 SI E	220-240	0.11	50/60	220	27-40	59	8.8	50	80

1、输入均为：220-240V~ 50/60Hz；



CHINA QUALITY CERTIFICATION CENTRE