



Ref. Certif. No

NO127869

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

LED Power Supply

Name and address of the applicant

Foshan Eaglerise Power Science & Technology (Shunde) Co., Ltd.
No.4, East Huanzhen Road, Beijiao Shunde, Foshan, Guangdong
China

Name and address of the manufacturer

Foshan Eaglerise Power Science & Technology (Shunde) Co., Ltd.
No.4, East Huanzhen Road, Beijiao Shunde, Foshan, Guangdong
China

Name and address of the factory

See next page(s)

Note: When more than one factory, please report on page 2

 Additional Information on Page 2

Ratings and Principal characteristics

PRI: LV supply: max. 0.46 A, 220-240 V~, 50/60 Hz
Centralized emergency power supply: 198-254 V DC
SEC: Max. 60.2 W, max. 1.40 A, 9-52 Vd.c. (under load), max. 60 Vd.c. (no-load). EOFI: 15%

Trademark /Brand (If any)



Customer's Testing Facility (CTF) Stage used

Model/Type Ref

FLS-xx-yyyy DALI2 LD1, FSS-60-1400 DALI2 LD1, FLS-xx-yyyy DALI2 LA1, FLS-xx-yyyy
DALI2 LS1

Additional information (If necessary may also be reported on Page 2)

 Additional Information on Page 2

A sample of the product was tested and found to be in conformity with

IEC 61347-1:2015, IEC 61347-1:2015/AMD1:2017
IEC 61347-2-13:2014, IEC 61347-2-13:2014/AMD1:2016

As shown in the Test Report Ref. No. which forms part of this Certificate

REP016297

This CB Test Certificate is issued by the National Certification Body

Philip Pedersen vei 11,
NO-1366 Lysaker, Norway
Date: 20-09-2023Signature: Sweet Yuan
Certification department



Ref. Certif. No

NO127869

Foshan Eaglerise Power Science & Technology (Shunde) Co., Ltd.
No.4, East Huanzhen Road, Beijiao Shunde, Foshan, Guangdong
China

EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD
West Zone, Ji An County Industrial Park, Ji an County
Jiangxi Province
China

Additional Information (if necessary)

SELV, constant current output, thermal protected 110 °C,
ta: 45 °C / 50 °C, tc: 75 °C / 80 °C / 85 °C / 90 °C

Independent type with terminal cover incl. strain relief, Class II;
Built-in type without terminal cover for FLS-26-700 DALI2 LD1, FLS-44-1050 DALI2 LD1, FSS-60-1400 DALI2 LD1.
Independent controlgear, Class II for FLS-25-700 DALI2 LA1, FLS-40-1050 DALI2 LA1, FLS-60-1400 DALI2 LA1,
FLS-25-700 DALI2 LS1, FLS-44-1050 DALI2 LS1, FLS-60-1400 DALI2 LS1.

The 'xx' in the type designation can be 25, 26, 40, 44, 60, indicating the approximate rated output wattage in Watt.

The 'yyyy' is for the output current and represents the number from 150 to 1400, for example, 150 means the output current is 150 mA, 1400 means the output current is 1400 mA.



Philip Pedersen vei 11,
NO-1366 Lysaker, Norway

Date: 20-09-2023

Signature: Sweet Yuan
Certification department