NFC APP

NFC APP INSTRUCTIONS

2022/12/10

Reading Data



- 1. Scan the QR code to download the NFC APP
- 2. Open the smart phone NFC function



1. Hold your phone tightly against the NFC position of the driver and

receive the NFC signal.

(Most NFC signals are concentrated on the top of the phone)

2. When the message 'Tag detected, please click read' is displayed, click

the 'Read' button, and the system prompts that the reading was

successful, indicating that the NFC device data has been read to the APP.





! Click on the first icon in the upper right corner to jump to device information.

0		ĒØ
	Mode Type Read FMS-100-700 N-S DALI-2 LN	
	Current CLO	
A	CH1 current Range : 200~700 mA	300 mA
	CH1 current set	
		300 MA
	🗐 Read	🗐 Write

<	Device Information
Mode Type	FMS-100-700 N-S DALI-2 LN
GTIN	6937220701148
Hardware Ve	ersion 1.0
Soft Version	1.0
Fixture ID	1410010129-3
Range One	200~700 mA
Current One	300 mA
Work Time	Oh
Driver Type	DT6



Setting Parameter

Setting current parameter



1. Choose the current to edit

E () Mode Type Read Current CLO Input 200-700 No Yes \bigtriangledown @ 3 2 $\langle \times \rangle$ 1 . \bigcirc 5 6 4 +7 8 9 -换行 , O 0 符号 返回

2. Enter the required current into the edit box

Mode 1: Change the parameter, write in the data



3. Put the phone NFC location tightly against the drive and click 'Write'to write in the current.

Setting Parameter

parameters Setting constant lumen



1. Click to open function switch, open the "Constant Lumen"

Ξ 0 Mode Type Read FMS-100-700 N-S DALI-2 LN Current **CLO** > 100 25 30 100 Curve Brightness (%) 60 40 20 40kh 60kh 80kh 20kh 100kh E Read 🗄 Write

2. Enter the required constant lumen data into the edit box

Mode 1: Change the parameter, write in the data



3. Put the phone NFC location tightly against the drive and click "WRITE to write in the current

Setting Parameter



1. Click the knob in the upper right corner to enter the design interface

you want to export the current configuration, you can click to save the configuration file and it will automatically create a new NFC folder on your phone to save the data.)

3. Search for NFC files in the overall mobile document

Mode 2:Import the configuration parameters, writing in the data

4. Select the configured file to import

5. After importing the file, return to the main interface and click "WRITE" to write into the driver

Note

Download the NFC-APP

1.If failed to download the app, please check if the smartphone	the
supports NFC function or contact the supplier's sales	canı
representative for further assistance	2.W
2.Eaglerise NFC APP is suitable for Android 42 and above versions	
3.When scanning through a smartphone, the LED driver does not	
need to be powered on.	
	the

Read the NFC driver data

1.Do not take the NFC device away, keep close to the smart	1.Do
phone	smar
2.If the prompt reads failed, you need to adjust the device	2.lf t
position and read multiple times	devid

Write NFC driver data

1.Please refer to the "range" between currents and enter

correct data. Any current that exceeds the "range" not be set.

/hen the main window clears the error data and shows ata error!" Please check it. The "range" may not meet specifications of the selected LED driver

3.When writing data, the phone should be put closely to the NFC driver

Read the NFC driver data

o not take the NFC device away, keep close to the art phone

the prompt reads failed, you need to adjust the

ice position and read multiple times