

# ATTESTATION OF CONFORMITY

Issued to: Foshan Eaglerise Power Science & Technology (Shunde)Co.,Ltd.  
No.4 East Huanzhen Road, Beijiao, Shunde, Foshan, Guangdong, China

For the product: LED power supply

Trade name: 

Type/Model: see annex

Ratings: see annex

Manufactured by: Foshan Eaglerise Power Science & Technology (Shunde)Co.,Ltd.  
No.4 East Huanzhen Road, Beijiao, Shunde, Foshan, Guangdong, China

Requirements: EN IEC 55015:2019 + A11:2020  
EN 61547:2009  
EN IEC 61000-3-2:2019 + A1:2021  
EN 61000-3-3:2013 + A1:2019 + A2:2021

This Attestation is granted on account of an examination by DEKRA, the results of which are laid down in a confidential file no 4911168.50.

This Attestation implies that the examined types are in accordance with the standards designated under the Electromagnetic Compatibility Directive (EMC) 2014/30/EU.

The examination has been carried out on one single specimen or several specimens of the product, submitted by the manufacturer. The Attestation does not include an assessment of the manufacturer's production. Conformity of his production with the specimen tested by DEKRA is not the responsibility of DEKRA.

The CE marking may be affixed on the product if all relevant and effective EC directives are complied with.

Arnhem, 5 December 2023

Number: 4911168.01AOC

DEKRA Testing and Certification (Shanghai) Ltd.,  
Guangzhou Branch



May Liu  
Certification Manager

© Integral publication of this attestation and adjoining reports is allowed



# Annex

Document no. : 4911168.01AOC

Type/Model:

| No.      | Model               | Input   |            |           | Output       |                |                 |          |
|----------|---------------------|---------|------------|-----------|--------------|----------------|-----------------|----------|
|          |                     | Voltage | Max.       | Frequency | Constant     | Normal working | No load working | Max.     |
|          |                     | (VAC)   | Current(A) | (Hz)      | current (mA) | voltage (Vdc)  | voltage (Vdc)   | Power(W) |
| Series 1 | LS-40-600 LI ADV    | 220-240 | 0.17       | 50/60     | 600          | 30-40          | 59              | 24       |
|          | LS-40-650 LI ADV    | 220-240 | 0.19       | 50/60     | 650          |                |                 | 26       |
|          | LS-40-700 LI ADV    | 220-240 | 0.2        | 50/60     | 700          |                |                 | 28       |
|          | LS-40-750 LI ADV    | 220-240 | 0.22       | 50/60     | 750          |                |                 | 30       |
|          | LS-40-800 LI ADV    | 220-240 | 0.23       | 50/60     | 800          |                |                 | 32       |
|          | LS-40-850 LI ADV    | 220-240 | 0.25       | 50/60     | 850          |                |                 | 34       |
|          | LS-40-900 LI ADV    | 220-240 | 0.26       | 50/60     | 900          |                |                 | 36       |
|          | LS-40-950 LI ADV    | 220-240 | 0.27       | 50/60     | 950          |                |                 | 38       |
|          | LS-40-1000 LI ADV   | 220-240 | 0.27       | 50/60     | 1000         |                |                 | 40       |
|          | LS-40-1050 LI ADV   | 220-240 | 0.29       | 50/60     | 1050         | 30-38.5        | 40.4            |          |
| Series 2 | LS-40-600 LI1 EXC   | 220-240 | 0.16       | 50/60     | 600          | 9-42           | 59              | 25.2     |
|          | LS-40-650 LI1 EXC   | 220-240 | 0.18       | 50/60     | 650          |                |                 | 27.3     |
|          | LS-40-700 LI1 EXC   | 220-240 | 0.19       | 50/60     | 700          |                |                 | 29.4     |
|          | LS-40-750 LI1 EXC   | 220-240 | 0.2        | 50/60     | 750          |                |                 | 31.5     |
|          | LS-40-800 LI1 EXC   | 220-240 | 0.22       | 50/60     | 800          |                |                 | 33.6     |
|          | LS-40-850 LI1 EXC   | 220-240 | 0.23       | 50/60     | 850          |                |                 | 35.7     |
|          | LS-40-900 LI1 EXC   | 220-240 | 0.24       | 50/60     | 900          |                |                 | 37.8     |
|          | LS-40-950 LI1 EXC   | 220-240 | 0.25       | 50/60     | 950          |                |                 | 39.9     |
|          | LS-40-1000 LI1 EXC  | 220-240 | 0.25       | 50/60     | 1000         |                |                 | 9-40     |
|          | LS-40-1050 LI1 EXC  | 220-240 | 0.27       | 50/60     | 1050         | 9-38.5         | 40.4            |          |
| Series 3 | LS-40-600 LI1-G EXC | 220-240 | 0.16       | 50/60     | 600          | 9-42           | 59              | 25.2     |
|          | LS-40-650 LI1-G EXC | 220-240 | 0.18       | 50/60     | 650          |                |                 | 27.3     |
|          | LS-40-700 LI1-G EXC | 220-240 | 0.19       | 50/60     | 700          |                |                 | 29.4     |
|          | LS-40-750 LI1-G EXC | 220-240 | 0.2        | 50/60     | 750          |                |                 | 31.5     |
|          | LS-40-800 LI1-G EXC | 220-240 | 0.22       | 50/60     | 800          |                |                 | 33.6     |

|          |                         |         |      |       |      |         |      |       |
|----------|-------------------------|---------|------|-------|------|---------|------|-------|
|          | LS-40-850 LI1-G<br>EXC  | 220-240 | 0.23 | 50/60 | 850  |         |      | 35.7  |
|          | LS-40-900 LI1-G<br>EXC  | 220-240 | 0.24 | 50/60 | 900  |         |      | 37.8  |
|          | LS-40-950 LI1-G<br>EXC  | 220-240 | 0.25 | 50/60 | 950  |         |      | 39.9  |
|          | LS-40-1000 LI1-G<br>EXC | 220-240 | 0.25 | 50/60 | 1000 | 9-40    |      | 40    |
|          | LS-40-1050 LI1-G<br>EXC | 220-240 | 0.27 | 50/60 | 1050 | 9-38.5  |      | 40.4  |
| Series 4 | LS-40-600 LI EXC S      | 220-240 | 0.17 | 50/60 | 600  | 24-42   | 59   | 25.2  |
|          | LS-40-650 LI EXC S      | 220-240 | 0.19 | 50/60 | 650  |         |      | 27.3  |
|          | LS-40-700 LI EXC S      | 220-240 | 0.2  | 50/60 | 700  |         |      | 29.4  |
|          | LS-40-750 LI EXC S      | 220-240 | 0.22 | 50/60 | 750  |         |      | 31.5  |
|          | LS-40-800 LI EXC S      | 220-240 | 0.23 | 50/60 | 800  |         |      | 33.6  |
|          | LS-40-850 LI EXC S      | 220-240 | 0.25 | 50/60 | 850  |         |      | 35.7  |
|          | LS-40-900 LI EXC S      | 220-240 | 0.26 | 50/60 | 900  |         |      | 37.8  |
|          | LS-40-950 LI EXC S      | 220-240 | 0.27 | 50/60 | 950  |         |      | 39.9  |
|          | LS-40-1000 LI EXC S     | 220-240 | 0.27 | 50/60 | 1000 |         |      | 24-40 |
|          | LS-40-1050 LI EXC S     | 220-240 | 0.29 | 50/60 | 1050 | 24-38.5 | 40.4 |       |

---

End