



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE NO.: 2022011002467749

NAME AND ADDRESS OF THE APPLICANT

Eaglerise Electric & Electronic (China) Co., Ltd.
No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong
Province, P.R.China

NAME AND ADDRESS OF THE MANUFACTURER

Eaglerise Electric & Electronic (China) Co., Ltd.
No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong
Province, P.R.China

NAME AND LOCATION OF THE FACTORY

Eaglerise Electric & Electronic (Ji An) Co., Ltd.
Southwest Corner, Crossing Between Panlong Road And Chaoyang Road, Industrial Park, Ji An
County, Jiangxi Province, P.R.China

PRODUCT NAME,MODEL AND SPECIFICATION

A.C. Supplied Electronic Controlgear For LED Modules (Independent, Constant Current Mode, SELV,
ta:50°C, Class II, IP20, Suitable For Direct Mounting On Normally Flammable Material, Temperature
Declared Thermally Protected:110°C)
See Appendix. 220-240V ~ 50/60Hz

STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB 17625.1-2022;GB/T 17743-2021;GB 19510.1-2009;GB 19510.14-2009

This is to certify that the above mentioned product(s) complies with the requirements of
implementation rules for compulsory certification(REFNO. CNCA-C10-01:2014).

Valid from: May.08,2024

Valid until: Mar.22,2027

Date of original issued: May.07,2022

The certificate information and validity could be checked by scanning the QR code below or logging in to
the website of the issuing authority, or on the website of the CNCA (www.cnca.gov.cn).

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P



SIGNATURE:

谢肇煦



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.





CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE NO. : 2022011002467749

Appendix : Page 1 of 2

序号	型号规格
tc:75°C	
1	LS-6-150 TRIAC LI (输出: 150mA, 27-42Vdc, Max.50Vdc, Max.6.3W)
2	LS-6-200 TRIAC LI (输出: 200mA, 20-30Vdc, Max.40Vdc, Max.6W)
3	LS-6-250 TRIAC LI (输出: 250mA, 16-24Vdc, Max.34Vdc, Max.6W)
4	LS-6-300 TRIAC LI (输出: 300mA, 13-20Vdc, Max.30Vdc, Max.6W)
5	LS-6-350 TRIAC LI (输出: 350mA, 12-17Vdc, Max.25Vdc, Max.6W)
6	LS-9-200 TRIAC LI (输出: 200mA, 27-42Vdc, Max.55Vdc, Max.8.4W)
7	LS-9-250 TRIAC LI (输出: 250mA, 25-38Vdc, Max.50Vdc, Max.9.5W)
8	LS-9-300 TRIAC LI (输出: 300mA, 20-30Vdc, Max.40Vdc, Max.9W)
9	LS-9-350 TRIAC LI (输出: 350mA, 17-27Vdc, Max.35Vdc, Max.9.5W)
10	LS-9-400 TRIAC LI (输出: 400mA, 15-23Vdc, Max.33Vdc, Max.9.2W)
11	LS-9-450 TRIAC LI (输出: 450mA, 13-20Vdc, Max.30Vdc, Max.9W)
12	LS-9-500 TRIAC LI (输出: 500mA, 12-19Vdc, Max.28Vdc, Max.9.5W)
tc:80°C	
13	LS-12-250 TRIAC LI (输出: 250mA, 32-48Vdc, Max.59Vdc, Max.12W)
14	LS-12-300 TRIAC LI (输出: 300mA, 26-40Vdc, Max.50Vdc, Max.12W)
15	LS-12-350 TRIAC LI (输出: 350mA, 23-35Vdc, Max.46Vdc, Max.12.3W)
16	LS-12-400 TRIAC LI (输出: 400mA, 20-30Vdc, Max.40Vdc, Max.12W)
17	LS-12-450 TRIAC LI (输出: 450mA, 17-27Vdc, Max.35Vdc, Max.12.2W)
18	LS-12-500 TRIAC LI (输出: 500mA, 16-24Vdc, Max.34Vdc, Max.12W)
19	LS-12-550 TRIAC LI (输出: 550mA, 14-22Vdc, Max.32Vdc, Max.12.1W)
20	LS-12-600 TRIAC LI (输出: 600mA, 13-20Vdc, Max.30Vdc, Max.12W)
21	LS-12-650 TRIAC LI (输出: 650mA, 12-18Vdc, Max.25Vdc, Max.11.7W)
22	LS-12-700 TRIAC LI (输出: 700mA, 12-18Vdc, Max.25Vdc, Max.12.6W)
23	LS-15-300 TRIAC LI (输出: 300mA, 35-50Vdc, Max.59Vdc, Max.15W)
24	LS-15-350 TRIAC LI (输出: 350mA, 27-42Vdc, Max.53Vdc, Max.14.7W)
25	LS-15-400 TRIAC LI (输出: 400mA, 25-38Vdc, Max.48Vdc, Max.15.2W)

This page is attached to the certificate and should be used at the same time as the certificate page.



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE NO. : 2022011002467749

Appendix : Page 2 of 2

26	LS-15-450 TRIAC LI (输出: 450mA, 22-33Vdc, Max.43Vdc, Max.14.9W)
27	LS-15-500 TRIAC LI (输出: 500mA, 20-30Vdc, Max.39Vdc, Max.15W)
28	LS-15-550 TRIAC LI (输出: 550mA, 17-27Vdc, Max.35Vdc, Max.14.9W)
29	LS-15-600 TRIAC LI (输出: 600mA, 16-25Vdc, Max.33Vdc, Max.15W)
30	LS-15-650 TRIAC LI (输出: 650mA, 16-23Vdc, Max.31Vdc, Max.15W)
31	LS-15-700 TRIAC LI (输出: 700mA, 14-22Vdc, Max.30Vdc, Max.15.4W)
32	LS-20-300 TRIAC LI (输出: 300mA, 50-68Vdc, Max.80Vdc, Max.20.4W)
33	LS-20-350 TRIAC LI (输出: 350mA, 40-60Vdc, Max.75Vdc, Max.21W)
34	LS-20-400 TRIAC LI (输出: 400mA, 32-50Vdc, Max.59Vdc, Max.20W)
35	LS-20-450 TRIAC LI (输出: 450mA, 27-42Vdc, Max.53Vdc, Max.18.9W)
36	LS-20-500 TRIAC LI (输出: 500mA, 27-42Vdc, Max.53Vdc, Max.21W)
37	LS-20-550 TRIAC LI (输出: 550mA, 25-38Vdc, Max.50Vdc, Max.20.9W)
38	LS-20-600 TRIAC LI (输出: 600mA, 22-34Vdc, Max.46Vdc, Max.20.4W)
39	LS-20-650 TRIAC LI (输出: 650mA, 20-30Vdc, Max.40Vdc, Max.19.5W)
40	LS-20-700 TRIAC LI (输出: 700mA, 20-30Vdc, Max.40Vdc, Max.21W)

输入: 220-240V~ 50/60Hz

This page is attached to the certificate and should be used at the same time as the certificate page.



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.