

NO131177

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE	
Product	LED Power Supply
Name and address of the applicant	EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD West Zone, Ji An County Industrial Park, Ji an County Jiangxi Province China
Name and address of the manufacturer	EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD West Zone, Ji An County Industrial Park, Ji an County Jiangxi Province China
Name and address of the factory	EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD West Zone, Ji An County Industrial Park, Ji an County Jiangxi Province China
Note: When more than one factory,please report on page 2	Additional Information on Page 2
Ratings and Principal characteristics	PRI: max. 0.3 A, 220-240 V~, 50/60 Hz; SEC: Max. 23.4 W, max. 0.7 A, 8-70 Vd.c. (under load), 90 Vd.c. (no load)
Trademark /Brand (If any)	(EAGLERISE), (ASTRA POWER)
	EAGLERISE + ASTRA
Customer's Testing Facility (CTF) Stage used	
Model/Type Ref	LS-xx-yyy SI1 E, LS-xx-yyy SI2 E
Additional information(If necessary may also be reported on Page 2)	Additional Information on Page 2
A sample of the product was tested and found to be in conformity with	IEC 61347-1:2015, IEC 61347-1:2015/AMD1:2017 IEC 61347-2-13:2014, IEC 61347-2-13:2014/AMD1:2016
As shown in the Test Report Ref. No. which forms part of this Certificate	REP043798
This CB Test Certificate is issued by the National Certification Body	
Nemko	
	OK hyun Joon
Philip Pedersen vei 11,	OF IMM SU

Signature: Okhyun Jeon Certification department

Disclaimer: This document is controlled and has been released electronically. Only the version on the IECEE Website is the current document version

NO-1366 Lysaker, Norway Date: 14-06-2024



Additional Information (if necessary)

Independent type, Class II, SELV, constant current output, thermal protected 110 °C, ta: 45 °C, tc: 75 °C / 80 °C / 85 °C.

The 'xx' in the type designation can be 8, 12 or 21.

The 'yyy' is for the output current and represents the number from 70 to 700, for example, 70 means the output current is 70 mA, 700 means the output current is 700 mA.



Philip Pedersen vei 11, NO-1366 Lysaker, Norway Date: 14-06-2024

OK hyun Joon

Signature: Okhyun Jeon Certification department

Disclaimer: This document is controlled and has been released electronically. Only the version on the IECEE Website is the current document version