



Ref. Certif. No

NO131818

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT  
(IECEE) CB SCHEME

## CB TEST CERTIFICATE

## Product

LED Power Supply

## Name and address of the applicant

EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD  
West Zone, Ji An County Industrial Park, Ji an County  
Jiangxi Province  
China

## Name and address of the manufacturer

EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD  
West Zone, Ji An County Industrial Park, Ji an County  
Jiangxi Province  
China

## Name and address of the factory

EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD  
West Zone, Ji An County Industrial Park, Ji an County  
Jiangxi Province  
China

Note: When more than one factory, please report on page 2

 Additional Information on Page 2Ratings and Principal characteristics  
Trademark /Brand (If any)PRI: max. 0.3 A, 220-240 V~, 50/60 Hz  
(EAGLERISE), (ASTRAPOWER)

## Customer's Testing Facility (CTF) Stage used

## Model/Type Ref

CS-xx-yyy SI, CS-xx-yyy LI, CS-xx-yyy TRIAC LI, CS-xx-yyy LI1

## Additional information (If necessary may also be reported on Page 2)

 Additional Information on Page 2

## A sample of the product was tested and found to be in conformity with

IEC 61347-1:2015, IEC 61347-1:2015/AMD1:2017  
IEC 61347-2-13:2014, IEC 61347-2-13:2014/AMD1:2016

## As shown in the Test Report Ref. No. which forms part of this Certificate

REP052191

This CB Test Certificate is issued by the National Certification Body

Philip Pedersen vei 11,  
NO-1366 Lysaker, Norway  
Date: 22-08-2024Signature: Juan Z Saussey  
Certification department



Ref. Certif. No

NO131818

### Additional Information (if necessary)

SEC: max. 42.0 W, max. 1.05 A, 9-50 Vd.c. (under load), max. 69 Vd.c. (no-load). Built-in LED power supply with double or reinforced insulation, providing SELV output, constant current output, thermally protected 110 °C. ta: 55 °C / 60 °C / 70 °C, tc: 90 °C / 95 °C / 100 °C.

#### CS-xx-yyy SI:

The 'xx' in the type designation can be 8, 15 or 22.

The 'yyy' is for the output current and represents the number from 80 to 550, for example, 80 means the output current is 80 mA, 550 means the output current is 550 mA.

#### CS-xx-yyy LI:

The 'xx' in the type designation can be 22, 30 or 42.

The 'yyy' is for the output current and represents the number from 350 to 1050, for example, 350 means the output current is 350 mA, 1050 means the output current is 1050 mA.

#### CS-xx-yyy TRIAC LI:

The 'xx' in the type designation can be 8, 15, 22 or 36.

The 'yyy' is for the output current and represents the number from 100 to 900, for example, 100 means the output current is 100 mA, 900 means the output current is 900 mA.

#### CS-xx-yyy LI1:

The 'xx' in the type designation can be 30 or 42.

The 'yyy' is for the output current and represents the number from 600 to 1050, for example, 600 means the output current is 600 mA, 1050 means the output current is 1050 mA.



Philip Pedersen vei 11,  
NO-1366 Lysaker, Norway

Date: 22-08-2024

Signature: Juan Z Saussey  
Certification department