



Ref. Certif. No

NO132240

## IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

## CB TEST CERTIFICATE

## Product

LED POWER SUPPLY

## Name and address of the applicant

EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD  
West Zone, Ji An County Industrial Park, Ji an County  
Jiangxi Province  
China

## Name and address of the manufacturer

EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD  
West Zone, Ji An County Industrial Park, Ji an County  
Jiangxi Province  
China

## Name and address of the factory

EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD  
West Zone, Ji An County Industrial Park, Ji an County  
Jiangxi Province  
China

Note: When more than one factory, please report on page 2

 Additional Information on Page 2

## Ratings and Principal characteristics

PRI: LV supply: Max. 0.9 A, 220-240 V~, 50/60 Hz; Centralized emergency power supply:  
220-240 V DC  
(EAGLERISE), (ASTRAPOWER)

## Trademark /Brand (If any)



## Customer's Testing Facility (CTF) Stage used

## Model/Type Ref

FMS-xxx-yyy N-S CCT LD EXC, FMS-xxx-yyy N-S LD1 E, FMS-xxx-yyy N-S DALI-2 LD,  
FMS-xxx-yyy N-S DALI-2 LN EXC

## Additional information (If necessary may also be reported on Page 2)

 Additional Information on Page 2

## A sample of the product was tested and found to be in conformity with

IEC 61347-1:2015, IEC 61347-1:2015/AMD1:2017  
IEC 61347-2-13:2014, IEC 61347-2-13:2014/AMD1:2016

## As shown in the Test Report Ref. No. which forms part of this Certificate

REP058702

This CB Test Certificate is issued by the National Certification Body

Philip Pedersen vei 11,  
NO-1366 Lysaker, Norway

Date: 12-10-2024

Signature: Sweet Yuan  
Certification department



Ref. Certif. No

NO132240

### Additional Information (if necessary)

SEC: Max. 150 W, Max. 1.05 A, 20-220 Vd.c. (under load), Max. 250 Vdc (no-load).

EOFI: 100% or EOFI: 15%. Built-in, constant current output, thermal protected 110 °C, ta: 50 °C / 60 °C, tc: 80 °C / 85 °C / 90 °C

FMS-xxx-yyy N-S CCT LD EXC:

The 'xxx' in the type designation can be 20, 40, 60, 80, 100 or 150.

The 'yyy' is for the output current and represents the number from 350, 500 or 700, for example, 350 means the output current is 350 mA, 700 means the output current is 700 mA.

FMS-xxx-yyy N-S LD1 E:

The 'xx' in the type designation can be 80, 100 or 150.

The 'yyy' is for the output current and represents the number from 350, 500 or 700, for example, 350 means the output current is 350 mA, 700 means the output current is 700 mA.

FMS-xxx-yyy N-S DALI-2 LD:

The 'xxx' in the type designation can be 35, 75, 100 or 150.

The 'yyy' is for the output current and represents the number from 350, 500 or 1050, for example, 350 means the output current is 350 mA, 1050 means the output current is 1050 mA.

FMS-xxx-yyy N-S DALI-2 LN EXC:

The 'xxx' in the type designation can be 35, 75, 100 or 150.

The 'yyy' is for the output current and represents the number from 350, 500 or 1050, for example, 350 means the output current is 350 mA, 1050 means the output current is 1050 mA.



Philip Pedersen vei 11,  
NO-1366 Lysaker, Norway

Date: 12-10-2024

Signature: Sweet Yuan  
Certification department