

## IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

## **CB TEST CERTIFICATE**

Product LED Power Supply

Name and address of the applicant EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD

West Zone, Ji An County Industrial Park, Ji an County

Jiangxi Province

China

Name and address of the manufacturer EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD

West Zone, Ji An County Industrial Park, Ji an County

Jiangxi Province

China

Name and address of the factory EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD

West Zone, Ji An County Industrial Park, Ji an County

Jiangxi Province

China

Note: When more than one factory,please report on page 2

☐ Additional Information on Page 2

Ratings and Principal characteristics

Trademark /Brand (If any)

PRI: max. 0.27 A, 220-240 V~, 50/60 Hz (EAGLERISE), (ASTRAPOWER)



**Customer's Testing Facility (CTF) Stage used** 

Model/Type Ref

CS-xx-yyyy LI1

Additional information(If necessary may also be reported on Page 2)

✓ Additional Information on Page 2

A sample of the product was tested and found

IEC 61347-1:2015, IEC 61347-1:2015/AMD1:2017 IEC 61347-2-13:2014, IEC 61347-2-13:2014/AMD1:2016

to be in conformity with

REP067754

As shown in the Test Report Ref. No. which forms part of this Certificate

This CB Test Certificate is issued by the National Certification Body

Nemko

Philip Pedersen vei 11, NO-1366 Lysaker, Norway Date: 28-11-2024

Signature: Juan Z Saussey

Certification department



## **Additional Information (if necessary)**

SEC: max. 42 W, max. 1.05 A, 24-42 Vd.c. (under load), max. 59 Vd.c. (no-load). Built-in LED power supply with double or reinforced insulation, providing SELV output, constant current output, thermally protected 110°C. ta: 70°C, tc: 100°C. The insulation between live parts and enclosure fulfils reinforced insulation, IP20, for indoor use. All models encapsulated by potting compound totally. In model name, the 'xx' in the type designation can be 24, 30 or 42. The 'yyyy' is for the output current and represents the number from 450 to 1050, for example, 450 means the output current is 450 mA, 1050 means the output current is 1050 mA.



Philip Pedersen vei 11, NO-1366 Lysaker, Norway Date: 28-11-2024

Signature: Juan Z Saussey

Certification department